

Printing date 30.05.2022 Version 3 Revision: 30.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: INSEBO Profi Neutralsilikon 25

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture Spacings sealent

1.3 Details of the supplier of the safety data sheet

WS INSEBO GmbH

Industriestraße 24, A-2325 Himberg bei Wien

Tel.: +43 (0) 2235/86227-0 Fax: +43 (0) 2235/86020 e-mail: office@insebo.com

1.4 Emergency telephone number Call local emergency information.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 void

Hazard pictograms void

Signal word void

Hazard statements void

Precautionary statements

P102 Keep out of reach of children.

Additional information:

EUH208 Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine, 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

2.3 Other hazards No further relevant information available.

SECTION 3: Composition/information on ingredients

3.2 Mixture

Description: Mixture of substances listed below with non-hazardous additions.

| Dangerous components: | | |
|---|---|----------|
| CAS: 112945-52-5 EC number: 601-216-3 | silica, amorphous, fumed substance with a Community workplace exposure limit | 10 - 25% |
| CAS: 37859-55-5 ELINCS: 484-460-1 Reg.No.: 01-2120004323-76 | O,O',O"-(methylsilylidyne)trioxime 2-pentanone Acute Tox. 4, H302; Eye Irrit. 2, H319 | < 5% |
| CAS: 1760-24-3 EINECS: 217-164-6 Reg.No.: 01-2119970215-39 | N-(3-(trimethoxysilyl)propyl)ethylenediamine Eye Dam. 1, H318; Skin Sens. 1, H317 | < 1% |
| CAS: 7727-43-7 EINECS: 231-784-4 Reg.No.: 01-2119491274-35 | barium sulfate substance with a Community workplace exposure limit | < 1% |



Printing date 30.05.2022 Version 3 Revision: 30.05.2022

Trade name: INSEBO Profi Neutralsilikon 25

| Г | CAS: 26530-20-1 | 2-octyl-2H-isothiazol-3-one | < 1% |
|---|-------------------|--|------|
| | EINECS: 247-761-7 | Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin | |
| | | Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); | |
| | | Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 | |
| | | Specific concentration limit: | |
| | | Skin Sens. 1A; H317: C ≥ 0.0015 % | |

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: In case of accident or if you feel unwell seek medical advice (show label where possible).

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothes. Rinse skin thoroughly with water and soap. In case of irritation seek medical treatment.

After eye contact:

Rinse opened eye for several minutes under running water. Get medical advice if irritation persists.

After swallowing:

Rinse out mouth with plenty of water. If symptoms of indisposition persist, seek medical advice.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

No special measures are required, use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of harmful gases (e.g. carbon oxides, COx) is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Use protective equipment suitable to the situation.

Additional information

Contain runoff to prevent entry into water or drainage systems.

Dispose of fire debris and contaminated firefighting water according to the regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Particular danger of slipping on leaked/spilled product.



Printing date 30.05.2022 Version 3 Revision: 30.05.2022

Trade name: INSEBO Profi Neutralsilikon 25

6.2 Environmental precautions:

Do not allow to enter sewers, surface or ground water.

Contain the spilled material by bunding.

Advise water authority in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid or universal binders, sawdust).

Allow to solidify and remove mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid eye and skin contact with the product.

Provide good ventilation/exhaustion at the workplace.

Wash hands before break and at the end of work.

Information about fire - and explosion protection: No further relevant information available.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Store in cool, dry place in tightly closed original containers.

Protected from moisture.

Information about storage in one common storage facility:

Do not store food, beverages and animal feeding stuffs in the storage area.

Further information about storage conditions:

Keep out of the reach of children and domestic animals.

Keep container tightly sealed.

7.3 Specific end use(s) Sealant

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Ingredients with | limit values that require monitoring at the workplace: |
|------------------|---|
| CAS: 7727-43-7 | barium sulfate |
| AGW (Germany) | Long-term value: 1.25* 10** mg/m³; 2(II);*alveolengängig**einatembar; AGS, DFG, Y |
| CAS: 112945-52- | 5 silica, amorphous, fumed |
| MAK (Austria) | Long-term value: 4E mg/m³; (resp. CAS 7631-86-9) |
| MAK (Germany) | Long-term value: 4E mg/m³; vgl. Abschn.V |

Regulatory information

MAK (Austria): GKV 2020, 156. Verordnung, 09.04.2021, Teil II

MAK (Germany): MAK- und BAT-Liste

AGW (Germany): TRGS 900



Printing date 30.05.2022 Version 3 Revision: 30.05.2022

Trade name: INSEBO Profi Neutralsilikon 25

8.2 Exposure controls

Appropriate engineering controls Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Avoid unnecessary contact with the product. Do not eat, drink or smoke at workplace.

Remove contaminated clothing and wash carefully before reuse.

Wash hands before break and at the end of work.

Respiratory protection: Not required if room is well-ventilated.

Hand protection Protective gloves recommended.

Material of gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Safety goggles recommended.

Body protection: Not required if handled properly.

Environmental exposure controls

Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| rum. | 1 asty |
|--|--------------------|
| Colour: | Grey |
| Odour: | Characteristic |
| Odour threshold: | Not determined |
| Boiling point or initial boiling point and boiling | |
| range: | Not determined. |
| Flammability: | Not applicable. |
| Lower and upper explosion limit: | No data available. |
| Flash point: | No data available |
| Decomposition temperature: | No data available. |
| pH: | No data available |
| Viscosity | |
| dynamic: | > 50 Pas |
| Solubility | |
| | |

water: Not miscible or difficult to mix.

Partition coefficient, n-octanol/water:No data available.Vapour pressure:Not determined.Vapour density:Not determined.Density: $\approx 1 \text{ g/cm}^3$

9.2 Other information

Explosive properties: Product does not present an explosion hazard.



Printing date 30.05.2022 Version 3 Revision: 30.05.2022

Trade name: INSEBO Profi Neutralsilikon 25

| Oxidising properties: | No data available. | |
|--|--------------------|--|
| Information with regard to physical hazard | classes | |
| Explosives | void | |
| Flammable gases | void | |
| Aerosols | void | |
| Oxidising gases | void | |
| Gases under pressure | void | |
| Flammable liquids | void | |
| Flammable solids | void | |
| Self-reactive substances and mixtures | void | |
| Pyrophoric liquids | void | |
| Pyrophoric solids | void | |
| Self-heating substances and mixtures | void | |
| Substances and mixtures, which emit flamma | able | |
| gases in contact with water | void | |
| Oxidising liquids | void | |
| Oxidising solids | void | |
| Organic peroxides | void | |
| Corrosive to metals | void | |
| Desensitised explosives | void | |

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable under recommended storage conditions.
- 10.3 Possibility of hazardous reactions No hazardous reactions known if used according to specifications.
- 10.4 Conditions to avoid Keep dry and avoid extreme temperatures and direct sun exposure.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: None under normal conditions of storage and use.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification: There are no product specific data on toxicology available.

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Not skin sensitising based on results on similar mixtures tested using bridging principles according to CLP Regulation Art 9 (4).

Tested in accordance with OECD Test guideline 406 "Buehler Test", study S 4793

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.



Printing date 30.05.2022 Version 3 Revision: 30.05.2022

Trade name: INSEBO Profi Neutralsilikon 25

STOT-single exposure Based on available data, the classification criteria are not met. **STOT-repeated exposure** Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: For the product there are no ecotoxicological data available.

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Do not dispose waste or remains together with domestic waste, do not empty into sink or toilet, hand over to hazardous waste disposers.

Small quantities of cured residue can be disposed of along with domestic waste according to local regulations.

European waste catalogue

08 04 09: waste adhesives and sealants containing organic solvents or other dangerous substances

Uncleaned packaging

Recommendation:

Cartridges/buckets/pouches should be emptied completely and should preferably be recycled or reused in compliance with the local/national regulations. Cartridges/buckets/pouches not emptied appropriately or remains have to be disposed of like the product.

SECTION 14: Transport information

| 14.1 UN number or ID number ADR, IMDG, IATA | void | |
|--|------|--|
| 14.2 UN proper shipping name ADR. IMDG. IATA | void | |



Printing date 30.05.2022 Version 3 Revision: 30.05.2022

Trade name: INSEBO Profi Neutralsilikon 25

| 14.3 Transport hazard class(es) | | |
|---|-------------------------|--|
| ADR, IMDG, IATA Class | void | |
| 14.4 Packing group ADR, IMDG, IATA | void | |
| 14.5 Environmental hazards: | not applicable | |
| 14.6 Special precautions for user | not required | |
| 14.7 Maritime transport in bulk according instruments | g to IMO not applicable | |
| UN "Model Regulation": | void | |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations: -

Classification according to VbF: No data available.

Water hazard class: Water hazard class (German Regulation) 1 (self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

Further information:

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008: Bridging principle "Substantially similar mixtures".

Date of previous version: 11.03.2022

Abbreviations and acronyms:

CLP: REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

CAS: Chemical Abstracts Service (division of the American Chemical Society)

EINECS: European Inventory of Existing Commercial Chemical Substances



Printing date 30.05.2022 Version 3 Revision: 30.05.2022

Trade name: INSEBO Profi Neutralsilikon 25

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

MAK: maximum concentration of a chemical substance in the workplace

AGW: occupational exposure limit

PBT: persistent, bioaccumulative and toxic properties vPvB: very persistent and very bioaccumulative properties

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

VbF: Ordinance on the storage of combustible liquids, Austria

Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1: Skin corrosion/irritation – Category 1

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Data compared to the previous version altered: Section 2.16