

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.07.2025

Version 1

Revision: 31.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: INSEBO AeroTec PU-Cleaner**UFI:** 5HPF-JC5H-PA2K-4NR0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / mixture Removes uncured PU foam residues

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

WS INSEBO GmbH

Industriestraße 24, A-2325 Himberg bei Wien

Tel.: +43 (0) 2235/86227-0

e-mail: office@insebo.com

1.4 Emergency telephone number

 Call local emergency information.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

acetone

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.07.2025

Version 1

Revision: 31.07.2025

Trade name: INSEBO AeroTec PU-Cleaner

P501 Dispose of contents/container in accordance with national regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards Formation of explosive air/vapour mixtures are possible.

Results of PBT and vPvB assessment

This mixture does not meet the PBT- or vPvB-criteria according to Regulation (EC) No 1907/2006.

SECTION 3: Composition/information on ingredients

3.2 Mixture
Description: Mixture of substances listed below with non-hazardous additions.

Dangerous components:

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.No.: 01-2119471330-49	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	55 - 75%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.No.: 01-2119472128-37	dimethyl ether Flam. Gas 1A, H220; Press. Gas (Comp.), H280	12 - 38%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.No.: 01-2119485395-27	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	9 - 28%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	3 - 11%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
General information:

In case of accident or if you feel unwell seek medical advice (show label where possible).

In case of unconsciousness place patient stably in side position for transportation.

Never give anything by mouth to an unconscious person.

After inhalation: Supply fresh air, keep warm and at rest. If symptoms persist seek medical advice.

After skin contact:

Remove contaminated clothes. Rinse skin thoroughly with water and soap. In case of irritation seek medical treatment.

After eye contact:

Remove contact lenses and rinse opened eyes for at least 15 minutes with plenty of water. If irritation persists seek medical advice.

After swallowing:

Not applicable under normal use.

Flush with copious amounts of water (only if person is not unconscious).

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.07.2025

Version 1

Revision: 31.07.2025

Trade name: INSEBO AeroTec PU-Cleaner

Do NOT induce vomiting: seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed

In case of inhalation: causes headache, drowsiness, dizziness, nausea, can cause unconsciousness.

After skin contact: frequently or prolonged skin contact may cause dermal irritation; degreases and dries skin.

After eye contact: irritation (redness, burning)

After ingestion: causes nausea, depression; may have an impact on the central nervous system.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment (decontamination, vital function), there is no specific antidote.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, extinguishing powder, sand, soil

Unsuitable extinguishing media: Full water jet

5.2 Special hazards arising from the substance or mixture

Product contains highly flammable vapours and liquids. Formation of smoke in case of fire; carbon oxides, soot, hydrocarbons and aldehydes can be released due to incomplete combustion and thermolysis.

Risk of bursting due to heat. Formation of explosive air/vapour mixtures are possible. Vapors are heavier than air. By distribution at ground level flash back to distant ignition sources is possible.

5.3 Advice for firefighters**Protective equipment:**

In case of fire wear self-contained respiratory equipment and full protective suit.

Do not inhale explosion gases or combustion gases.

Additional information

Cool containers in the vicinity with water spray. Contain runoff to prevent entry into water or drainage systems.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Please notice instructions for person-related safety precautions, wear protective equipment (see 8.)

Avoid inhalation and contact with skin and eyes.

Do not breathe spray.

Ensure adequate ventilation.

Remove ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers, surface or ground water.

Contain the spilled material by bunding.

Advise water authority in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up

Absorb with non-combustible absorbent material, (eg sand, diatomite, vermiculite).

Collect for recovery or disposal in suitable receptacles.

Clean affected area with plenty of water and detergent. Collect rinse water in labelled salvage container for disposal according to the regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.07.2025

Version 1

Revision: 31.07.2025

Trade name: INSEBO AeroTec PU-Cleaner

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

While handling pay attention to the usual precaution for chemicals. Comply with instructions for use.

Use only in well ventilated areas.

Do not breathe fumes/aerosol.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke when using this product.

Wash hands before breaks and at the end of work.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights.

Do not pierce or burn, even after use.

Do not spray on an open flame or glowing objects.

Protect against electrostatic charges.

Formation of explosive air/vapour mixtures are possible.

Use only non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Store product in tightly closed original packaging in a cool, dry and well-ventilated place.

Storage regulations for pressurized gas receptacles must be observed.

Information about storage in one common storage facility:

Do not store food, beverages and animal feeding stuff in the storage area.

Store away from oxidizing and self-igniting materials.

Further information about storage conditions:

Keep out of the reach of children and domestic animals.

Protect from heat and direct sunlight.

7.3 Specific end use(s) Use only according to instructions.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 67-64-1 acetone

IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm
MAK (Austria)	Short-term value: 4800 mg/m ³ , 2000 ppm; Long-term value: 1200 mg/m ³ , 500 ppm
AGW (Germany)	Long-term value: 1200 mg/m ³ , 500 ppm; 2(I);AGS, DFG, EU, Y

CAS: 115-10-6 dimethyl ether

IOELV (EU)	Long-term value: 1920 mg/m ³ , 1000 ppm
MAK (Austria)	Short-term value: 3820 mg/m ³ , 2000 ppm; Long-term value: 1910 mg/m ³ , 1000 ppm
AGW (Germany)	Long-term value: 1900 mg/m ³ , 1000 ppm; 8(II);DFG, EU

CAS: 75-28-5 isobutane

MAK (Austria)	Short-term value: 3800 mg/m ³ , 1600 ppm; Long-term value: 1900 mg/m ³ , 800 ppm
---------------	--

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.07.2025

Version 1

Revision: 31.07.2025

Trade name: INSEBO AeroTec PU-Cleaner

AGW (Germany)	Long-term value: 2400 mg/m ³ , 1000 ppm; 4(II);DFG
CAS: 74-98-6 propane	
MAK (Austria)	Short-term value: 3600 mg/m ³ , 2000 ppm; Long-term value: 1800 mg/m ³ , 1000 ppm
AGW (Germany)	Long-term value: 1800 mg/m ³ , 1000 ppm; 4(II);DFG

Regulatory information

IOELV (EU): (EU) 2019/1831

MAK (Austria): GKV 2021, 330. Verordnung, 02.12.2024, Teil 2

AGW (Germany): TRGS 900

DNELs:

Acetone (CAS 67-64-1):

 worker, short-term exposure - local effects, inhalation 2420 mg/m³

 worker, long-term exposure - systemic effects, inhalation 1210 mg/m³

worker, long-term exposure - systemic effects, dermal 186 mg/kg bw/day

consumer, long-term exposure - systemic effects, dermal, oral 62 mg/kg bw/day

 consumer, long-term exposure - systemic effects, inhalation 200 mg/m³
PNECs:

Acetone (CAS 67-64-1)

Freshwater 10.6 mg/l, marine water 1.06 mg/l

Sediment freshwater 30.4 mg/kg, marine water 3.04 mg/kg

Intermittent releases 21 mg/l; STP 19.5 mg/l; soil 0.112 mg/kg

Ingredients with biological limit values:
CAS: 67-64-1 acetone

BGW (Germany)	50 mg/l
	Untersuchungsmaterial: Urin
	Probennahmezeitpunkt: Expositionsende bzw. Schichtende
	Parameter: Aceton

Regulatory information BGW (Germany): TRGS 903

8.2 Exposure controls
Appropriate engineering controls Provide good ventilation or exhaust at work.

Individual protection measures, such as personal protective equipment
General protective and hygienic measures:

Avoid unnecessary contact with the product. Do not eat, drink or smoke at workplace and keep it tidy.

Do not breathe gas/vapours/spray.

Remove contaminated clothing and wash carefully before reuse.

Store protective clothing separately.

Pregnant women should strictly avoid inhalation or skin contact.

Wash hands before break and at the end of work.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators (EN 141, Filtre type A).

Hand protection


Chemical resistant gloves (EN 374)

Dispose of when contaminated inside, when perforated or when contamination outside cannot be removed.

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.07.2025

Version 1

Revision: 31.07.2025

Trade name: INSEBO AeroTec PU-Cleaner
Material of gloves

The glove material has to be impermeable and resistant to the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection


Safety glasses with side shields (EN 166)

Ensure eye bath is to hand.

Body protection Protective work clothing

Environmental exposure controls

Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form:	Fluid
Colour:	Colourless
Odour:	Solvent-like
Melting point/freezing point:	-94.7 °C (acetone)
Boiling point or initial boiling point and boiling range:	55.8 - 56.6 °C (acetone) -40 - -10 °C (propellant)
Flammability:	Extremely flammable.
Lower and upper explosion limit:	
Lower:	1.1 Vol % (propellant)
Upper:	13 Vol% (propellant)
Flash point:	-18 °C (acetone) approx. -80 °C (propellant)
Auto-ignition temperature:	465 °C (acetone)
Decomposition temperature:	Not determined.
pH:	Not determined.
Viscosity	
kinematic:	Not determined.
Solubility	
water:	Partly soluble.
Partition coefficient, n-octanol/water at 20 °C:	-0.24 log Kow (acetone)
Vapour pressure:	< 0.7 MPa
Density:	approx. 0.8 g/cm ³
Relative vapour density	Not determined.

9.2 Other information
VOC (EC): approx. 1 kg/kg

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.07.2025

Version 1

Revision: 31.07.2025

Trade name: INSEBO AeroTec PU-Cleaner
Information with regard to physical hazard classes
Aerosols

Extremely flammable aerosol. Pressurised container: May burst if heated.

SECTION 10: Stability and reactivity

10.1 Reactivity Stable under recommended transport or storage conditions.

10.2 Chemical stability No hazardous reaction when handled and stored according to provisions.

10.3 Possibility of hazardous reactions

Danger of receptacles bursting because of high vapour pressure when heated.
Exothermic reaction with strong acids.

10.4 Conditions to avoid

Heat, open flames, static electricity, under standard conditions of use hazardous reactions are not known.

10.5 Incompatible materials Strong acids and oxidising agents.

10.6 Hazardous decomposition products

Formation of smoke in case of fire; carbon oxides, soot, hydrocarbons and aldehydes can be released due to incomplete combustion and thermolysis.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

There are no product specific data on toxicology available.

CAS: 67-64-1 acetone

oral	LD50	5800 mg/kg (rat) (OECD 401, ECHA)
dermal	LD50	7400 mg/kg (rabbit) (ECHA)
inhalative	LC50/4h	> 20 mg/l (rat) (ECHA)

Skin corrosion/irritation

Based on available data, the classification criteria are not met.
Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.07.2025

Version 1

Revision: 31.07.2025

Trade name: INSEBO AeroTec PU-Cleaner

Aspiration hazard Based on available data, the classification criteria are not met.

Experience with humans:

In case of inhalation: causes headache, drowsiness, dizziness, nausea, can cause unconsciousness.

After skin contact: frequently or prolonged skin contact may cause dermal irritation; degreases and dries skin.

After eye contact: irritation (redness, burning)

After ingestion: causes nausea, depression; may have an impact on the central nervous system.

11.2 Information on other hazards

Endocrine disrupting properties None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

For the product there are no ecotoxicological data available.

CAS: 67-64-1 acetone

EC12/0.5h	1000 mg/l (activated sludge) (ECHA)
LOEC/8d	530 mg/l (bacteria, <i>Microsystis aeruginosa</i>) (ECHA)
LC50/48h	8800 mg/l (water flea, <i>Daphnia pulex</i>) (ECHA)
LC50/96h	5540 mg/l (rainbow trout, <i>Oncorhynchus mykiss</i>) (OECD 203; ECHA)
NOEC/96h	430 mg/l (<i>Prorocentrum minimum</i>) (ECHA)
NOEC/28d	2212 mg/l (water flea, <i>Daphnia magna</i>) (ECHA)

12.2 Persistence and degradability

Biodegradable

Acetone: Biodegradation 91 % (28 days, OECD 301 B)

12.3 Bioaccumulative potential The product has a low potential for bioaccumulation.

12.4 Mobility in soil High mobility

12.5 Results of PBT and vPvB assessment Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects Avoid release to the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Do not dispose waste or remains together with domestic waste, do not empty into sink or toilet, hand over to hazardous waste disposers.

European waste catalogue

16 05 04: Gases in pressure containers (including halons) containing dangerous substances

15 01 10 : Packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging

Recommendation:

Disposal must be made according to official regulations.

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.07.2025

Version 1

Revision: 31.07.2025

Trade name: INSEBO AeroTec PU-Cleaner

Containers not emptied completely have to be disposed of as hazardous waste and not together with household waste.
Do not pierce or burn, even after use.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

ADR

1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR



Class

2 5F Gases.

Label

2.1

IMDG, IATA



Class

2.1 Gases.

Label

2.1

14.4 Packing group

ADR, IMDG, IATA

void

14.5 Environmental hazards

not applicable

14.6 Special precautions for user

Warning: Gases.

Hazard identification number (Kemler code):

-

14.7 Maritime transport in bulk according to IMO

instruments

not applicable

UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
Seveso category P3a FLAMMABLE AEROSOLS

Regulation (EU) 2019/1148: The product is subject to Regulation (EU) 2019/1148, Article 9.

VOC (EC): ≈ 1 kg/kg

Classification according to VbF: Void

Water hazard class: Water hazard class (German Regulation) 1 (self-assessment): slightly hazardous for water.

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.07.2025

Version 1

Revision: 31.07.2025

Trade name: INSEBO AeroTec PU-Cleaner**15.2 Chemical safety assessment** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further information:

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008: Calculation method

Abbreviations and acronyms:

CLP: REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
UFI: Unique Formula Identifier
CAS: Chemical Abstracts Service (division of the American Chemical Society)
EINECS: European Inventory of Existing Commercial Chemical Substances
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
AGW: occupational exposure limit
MAK: maximum concentration of a chemical substance in the workplace
IOELV: indicative occupational exposure limit values (EU)
DNEL: Derived No-Effect Level
PNEC: Predicted No-Effect Concentration
ECHA: European Chemicals Agency
LC50: lethal concentration, 50%
LD50: lethal dose, 50%
EC50: maximal effective concentration, 50%
LOEL/LOEC: lowest observed effect level/concentration
NOEC: no observed effect concentration
OECD: Organisation for Economic Co-operation and Development
log Pow, Kow: partition coefficient (n-octanol/water)
PBT: persistent, bioaccumulative and toxic properties
vPvB: very persistent and very bioaccumulative properties
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
VOC: Volatile Organic Compounds
VbF: Ordinance on the storage of combustible liquids, Austria
REACH: Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Data compared to the previous version altered: -