

**PROFESSIONAL INSULATING,
SEALING AND BONDING**

**PRODUCT CATALOGUE
2024 / 2025**

**Variety from Austria: the right
solution for every purpose**

WS INSEBO GmbH
Industriestraße 24
A-2325 Himberg

Tel.: +43 2235 / 86227 - 0
E-Mail: office@insebo.com
Website: insebo.com

WE ARE WS INSEBO – AND YOU ARE VERY WELCOME!



Alexander Auerbach-Spielberger
Managing Partner

Based in Austria and valued globally, we passionately support you in your construction projects.

We are proud to be a respected Austrian provider of high-quality construction chemistry, and our commitment to excellence remains unwavering.

While the brand INSEBO® is new, it carries forward decades of tradition from our company, infused with modern strength. Our driving force is our aspiration to be the best in everything we do. With a diverse product portfolio and specialized expertise, WS INSEBO is a reliable partner for our customers.

Our family-run company's strong foundation is built on well-trained, long-term employees, decades of industry experience, and a robust sense of innovation. This combination ensures our continued success in the future.

Our greatest ambition is to have enthusiastic customers worldwide, and we are dedicated to achieving that goal.



Dipl.-Wirt.-Ing. Wolfgang Blumschein
CEO

Our customers take center stage in all our actions, ideas, initiatives, and efforts.

We are renowned for our high degree of flexibility, consistently achieving the seemingly impossible and going the extra mile for our clients.

Our commitment is to actively listen to our customers, comprehending their evolving needs and staying attuned to industry trends. This allows us to collaboratively provide suitable solutions.

We invite you to participate in this ongoing dialogue with us!

TABLE OF CONTENTS

4	Button description
5	Your Management-Team
6	Company
8	Sealants and accessories
32	Adhesives
40	PU-Foams and accessories
58	Joint sealing tapes
72	Lubricants, sprays & cleaners
76	Processing tools
84	General sales conditions

Tested product properties:

In this catalogue, the following symbols are used for labelling:



Flame retardant product tested according to DIN 4102 or EN 13501



Normally flammable product tested according to DIN 4102 or EN 13501



Germany-wide recycling system for used PU foam cans
For further details visit www.pdr.de



Noise tested product



Tested thermal insulation properties



System tested product for INSEBO[®] window connection systems according to ÖNORM B 5320



Tested for foam adhesives for External Thermal Insulation Composite Systems (ETICS)
For further details visit www.eota.eu



Tested airtightness



Tested driving rain tightness



Tested food compatibility



Mirror bonding



This product meets the requirements for ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.).



This product meets the highest requirements for pre-compressed joint sealing tapes according to DIN 18542 (BG1), both for window installations according to ÖNORM B 5320 and for facade sealings according to ÖNORM B 6400, as well as for other construction connection joints.



This product meets all requirements for not directly weathered, pre-compressed joint sealing tapes according to DIN 18542 (BG2) both for window installations according to ÖNORM B 5320 and for other (construction) connection joints.



This product meets all requirements for not directly weathered, precompressed multi-functional joint sealing tapes and the increased requirements for airtightness on the room side according to DIN 18542 (MF2) both for window installation according to ÖNORM B 5320 and for other (construction) connection joints.



CE-marked sealant with Declaration of Performance according to EN 15651



Over many years EMICODE[®] EC1 has proven itself as a standard for very low emission products. All products awarded with this sign fulfill very high environmental and health claims. For further details visit www.emicode.com



Since 2010, EMICODE[®] EC1^{PLUS} is the new, even stricter category for very low emission products. For further details visit www.emicode.com



The online platform baubook.info pursues the goal of supporting ecological building and renovation by means of targeted product information. Products marked with this button were evaluated according to the criteria given there.



The French VOC label indicates the number of emissions a product emits. The labelling is based on concentration limits for formaldehyde and 10 other individual substances as well as for the sum of VOCs (TVOCs).



Tested sealant for window glazing



PU foam with a content of < 0.1% free isocyanates. The training obligation from 24.08.2023 for safe industrial or commercial use concerns products with > 0.1% free isocyanates.

Values that we embody and are eager to share with you.

As an Austrian quality provider, we consistently recognize our responsibility to our customers.

One of the core values we live by daily is our high technical competence. Our ongoing success story is shaped by maintaining short response and delivery times, fostering a culture of innovation, producing exceptional products, and offering them at fair prices.

Our commitment to healthy growth and climate-friendly development is evident in our close collaboration with management. As a long-standing team of authorized signatories, we work together with our dedicated employees to preserve what has been tried and tested while continually pushing ourselves to evolve. Our well-coordinated procurement team, with extensive experience, shares the same goal of upholding proven practices while embracing ongoing development.

Our recent investments underscore our dedication to sustainability and future security. Since the beginning of 2023, our plant in Himberg near Vienna has been generating its own solar power, and half of our fleet is now electric. Furthermore, we have expanded our production capacities. Alongside our established classics, this catalogue highlights numerous new products.

We eagerly anticipate the new season and the opportunities it brings, and we look forward to sharing it with you!

Your Management-Team



ppa. Ing. Wolfgang Wodak
Head of Production Management

ppa. Vesna Rumpold-Bosteale, MA
Head of Sales Management

i.V Dr. Richard Holzner
Head of Product Management and Laboratory

WHAT WE CAN DO FOR YOUR PROJECT

One company - many advantages

We didn't become who we are overnight. We have built it up over decades through dedicated collaboration: as a multi-professional team, with our customers and suppliers, constantly striving to improve. Below is an overview of what we are willing to give in return

Service

We make things as easy as possible for our customers.

- **Customer care**
Our service and solution-oriented approach shine when handling inquiries about offers and orders.
- **Delivery reliability**
We don't talk about service - we live it. This includes meeting our deadlines.
- **Incognito on demand**
If you wish, we can deliver to your customers incognito, ensuring that the delivery is solely attributed to your company.
- **long-term stable team**
We maintain fair and enduring relationships with our employees, ensuring that our customers' contact persons remain unchanged over the years.
- **Marketing and point of sales service**
We support your sales by bringing customers into the store - and our store set-up expertise and ready-made advertising and display materials right along with it.

Values

Lived values, honest information.

- **Private owner**
Our company is privately owned, the size of its team is manageable and managed in a value-oriented manner.
- **Honesty inside and out**
We provide honest declarations, full transparency, and lived values.
- **Appreciative handling**
We treat all of our customers, employees and suppliers with the same level of appreciation and respect.
- **Value creation in Austria**
The people in our region should benefit from what we do and what we achieve. Our company headquarters including laboratory, warehouse and production facility are based in Austria. And that is where they will remain in the future.

Individuality

Solutions as flexible as you are.

- **Special requests**
Made exactly for your needs: We design your product and your solution.
- **Small-scale production**
Demand-based volumes: even the production of small quantities is part of our service.
- **Only what is needed**
We also sell by the box because not every project requires a large quantity.

Competence

We research, learn and know.

- **Technical questions**
We strive to fulfil your requests quickly and competently. We are particularly convincing when it comes to sealing compounds, adhesives, PU foams and accessories as well as standard-compliant window installations.
- **Own laboratory**
At our location near Vienna we research, develop and improve products in-house.
- **Training**
Over the course of the years, we have acquired comprehensive know-how and are happy to share this knowledge with you. Ask us about training courses at your location, virtually or in-house.
- **Collaborative project processing**
We're by your side for your construction project. In person and on site.
- **Quality right from the start**
We purchase raw materials from reliable partners, whose understanding of quality is as strict as our own.
- **Special knowledge**
We have experts in-house for chemicals law, transport regulations, packaging guidelines, CE marking and other areas. If necessary, we can supplement our own team of experts with specialized professionals from our large network of experts and testing institutes.

Operational strength

We are real go-getters.

- **Flexibility**
Our efficient, family-like structure allows us to react, produce, and deliver quickly.
- **Speed**
Short reaction times, handpicked logistics partners: we deliver goods in stock almost always within two working days throughout Austria. What we do not have in stock, we produce as quickly as possible.
- **Agreements**
We store your products and deliver them to you on demand within two working days. We fill in any gaps that arise in the stock level through rapid reproduction.
- **Private label production**
We produce your own brand - with extremely flexible box and pallet sizes, label designing and a number of optional additional services.
- **Trade shows**
You can find us at trade fairs and as supporters of your own in-house exhibitions.

Security

What we do, protects our customers.

- **Standard conformity**
We know the standards, we understand them and we help shaping them - through our association work, for example at FEICA, FCIO, QG-WDS and ÖNORM.
- **Cooperation with testing institutes**
We work closely with renowned testing institutes - such as Holz-forschung Austria, IBS Linz, ift Rosenheim, TU Graz, MA 39 or OFI Vienna.
- **Audits**
Regular audits (also on behalf of our customers) are an integral part of our quality management.
- **Complete examination**
We check every single production batch before going out for sale.
- **Product documentation**
All relevant information about our products, such as safety data sheets, declarations of performance and technical leaflets, can be found on our website on a daily basis and ready to download.
- **No unpleasant surprises**
With our focus on product and legal security, our customers are also on the safe side.

PRODUCT OVERVIEW

SEALANTS

When nothing should go in, out, or through in the end: Seal it up - with sealing compounds from INSEBO®.

INSEBO® sealants are made of high-quality silicones and acrylates and accompany you through construction and renovation. We also offer specialty products for windows, facades, natural stone, switchboards and parquet flooring.

- 10 Profi Sanitärsilikon 25
- 11 Sanitärsilikon
- 12 Silikon A
- 12 Silikon HT
- 13 Silikon SL
- 14 Silikon FO
- 15 Fassadenanschluss
- 15 Silikon GLF **NEW!**
- 16 Profi Neutralsilikon 25
- 17 Universalsilikon + Stein
- 17 Universalsilikon matt
- 18 Silikon SF
- 18 Silikon N Basic
- 18 Schalungssilikon
- 19 MS PowerFlex 25
- 20 MS Putzstruktur **NEW!**
- 21 MS Hybrid
- 21 MS Transparent
- 22 Acrylat D
- 22 Acrylat AC
- 23 Maleracryl
- 23 Acrylat Basic
- 24 Acrylat RF
- 24 Acrylat SF
- 25 Parkettfugenmasse
- 26 Spenglermasse
- 26 Grundierung OP
- 26 Grundierung GP
- 27 Glättmittel
- 27 Clipdüsen für Kartuschen 5 Stk. SB-Packung
- 27 Spezialdüsen-Set SB-Packung
- 28 Flächendüse **NEW!**
- 28 Verbindungsstück für Alubeutel **NEW!**
- 28 Verbindungsstück für Kartuschen **NEW!**
- 29 Statikmischer
- 30 PE-Rundschnüre
- 31 Drahtaufsteller
- 31 Kartuschendispenser 5x5
- 31 Kartuschendispenser 8x6

For more information about our products and the correct application please observe our technical and safety data sheets which you can read and download conveniently on our website (insebo.com).

Profi Sanitärsilikon 25

top silicone for the bathroom and kitchen

- acetate-crosslinking, highly elastic sealant
- suitable for aluminum, ceramics, glass and plastic in kitchen, sanitary and wet areas
- highest elasticity
- suitable for floor, wall and ceiling joints
- anti-mold-tested according to ISO 846
- elongation at break according to EN 8339: 300 %
- tested food compatibility
- temperature resistant up to +180 °C
- UV and ageing resistant
- color stable
- excellent processability
- high abrasion resistance
- waterproof
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)
- very low emission – EMICODE EC1^{PLUS}

Order designation	Cartridge 300 ml	Bag 400 ml
□ Profi Sanitärsilikon 25 transparent	202-250	* / **
□ Profi Sanitärsilikon 25 perlweiß	202-251	202-350
□ Profi Sanitärsilikon 25 pergamon altweiß	202-267	* / **
■ Profi Sanitärsilikon 25 fugen grau	202-292	202-353
■ Profi Sanitärsilikon 25 altsilber	202-290	202-352
■ Profi Sanitärsilikon 25 manhattan	202-252	* / **
■ Profi Sanitärsilikon 25 grau weiß	202-269	202-354
■ Profi Sanitärsilikon 25 silber grau	202-279	202-351
■ Profi Sanitärsilikon 25 dark manhattan	202-256	* / **
■ Profi Sanitärsilikon 25 mittel grau	202-270	202-355
■ Profi Sanitärsilikon 25 stein grau	202-253	202-357
■ Profi Sanitärsilikon 25 grau	202-258	* / **
■ Profi Sanitärsilikon 25 flanel grau	202-299	202-356
■ Profi Sanitärsilikon 25 achat grau	202-295	* / **
■ Profi Sanitärsilikon 25 beton grau	202-296	202-360
■ Profi Sanitärsilikon 25 stahl grau	202-298	202-361
■ Profi Sanitärsilikon 25 seiden grau	202-263	* / **
■ Profi Sanitärsilikon 25 sand grau	202-255	202-359
■ Profi Sanitärsilikon 25 sanitär grau	202-297	202-358
■ Profi Sanitärsilikon 25 basalt dunkelgrau	202-265	202-362
■ Profi Sanitärsilikon 25 anthrazit	202-264	* / **
■ Profi Sanitärsilikon 25 schwarz	202-259	* / **
■ Profi Sanitärsilikon 25 jasmin cremeweiß	202-257	* / **
■ Profi Sanitärsilikon 25 fugen weiß	202-273	* / **
■ Profi Sanitärsilikon 25 bahama beige	202-254	* / **
■ Profi Sanitärsilikon 25 natura	202-291	* / **
■ Profi Sanitärsilikon 25 camel beige	202-268	* / **
■ Profi Sanitärsilikon 25 sand beige	202-294	* / **
■ Profi Sanitärsilikon 25 wüsten beige	202-293	* / **
■ Profi Sanitärsilikon 25 miel ockerbraun	202-266	* / **
■ Profi Sanitärsilikon 25 terra cotta	202-260	* / **
■ Profi Sanitärsilikon 25 mittel braun	202-261	* / **
■ Profi Sanitärsilikon 25 bali dunkelbraun	202-262	* / **

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
*Not in stock | **Product on request | Bags (600 ml) on request



Sanitärsilikon

highly elastic silicone - ideal for the bathroom

- acetate-crosslinking, highly elastic sealant
- suitable for aluminum, ceramics, glass and plastic in kitchen, sanitary and wet areas
- anti-mold-tested according to ISO 846
- elongation at break according to EN 8339: 280 %
- tested food compatibility
- temperature resistant up to +150 °C
- UV and ageing resistant
- good processability
- waterproof


Order designation	Cartridge 300 ml
□ Sanitärsilikon transparent	202-001
□ Sanitärsilikon perlweiß	202-061
□ Sanitärsilikon pergamon altweiß	202-104
■ Sanitärsilikon fugen grau	202-132
■ Sanitärsilikon altsilber	202-130*
■ Sanitärsilikon manhattan	202-062
■ Sanitärsilikon grau weiß	202-126*
■ Sanitärsilikon silber grau	202-129*
■ Sanitärsilikon dark manhattan	202-122
■ Sanitärsilikon mittel grau	202-127*
■ Sanitärsilikon stein grau	202-116
■ Sanitärsilikon grau	202-063
■ Sanitärsilikon flanel grau	202-139*
■ Sanitärsilikon achat grau	202-135*
■ Sanitärsilikon beton grau	202-136*
■ Sanitärsilikon stahl grau	202-138*
■ Sanitärsilikon seidengrau	202-105
■ Sanitärsilikon sand grau	202-112*
■ Sanitärsilikon sanitär grau	202-137*
■ Sanitärsilikon basalt dunkelgrau	202-124
■ Sanitärsilikon anthrazit	202-117
■ Sanitärsilikon schwarz	202-064
■ Sanitärsilikon jasmin cremeweiß	202-009
■ Sanitärsilikon fugen weiß	202-128*
■ Sanitärsilikon bahama beige	202-011
■ Sanitärsilikon natura	202-131*
■ Sanitärsilikon camel beige	202-125
■ Sanitärsilikon sand beige	202-134*
■ Sanitärsilikon wüsten beige	202-133*
■ Sanitärsilikon terra cotta	202-106
■ Sanitärsilikon miel ockerbraun	202-118
■ Sanitärsilikon mittelbraun	202-123
■ Sanitärsilikon bali dunkelbraun	202-107

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
Bags (400 and 600 ml) on request | *Not in stock

Silikon A

cost-effective alternative for sanitary and kitchen

- acetate-curing silicone for sealings between stainless steel, aluminum, ceramic and glass
- rapid skin formation and curing
- anti-mold-tested according to ISO 846
- elongation at break according to EN 8339: 250 %
- temperature resistant up to +150 °C
- UV and ageing resistant

Order designation	Cartridge 300 ml
 Silikon A transparent	205-001
 Silikon A weiß	205-002
 Silikon A grau	205-007
 Silikon A dunkelbraun	205-015












Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



Silikon SL

highly elastic particularly versatile sealant based on alkoxy

- neutral-crosslinking, highly elastic sealant based on alkoxy
- suitable for metal construction, wood, glass, plastic, concrete, plaster, masonry, ceramics and many other building materials
- also applicable on damp surfaces
- for sealings of window connections according to ÖNORM B 5320
- highest elasticity
- elongation at break according to EN 8339: 300%
- temperature resistant up to +180 °C
- UV and ageing resistant
- very good smoothing properties
- odorless
- meets the requirements of ecological building materials
- very low emission – EMICODE EC1^{PLUS}

Order designation	Cartridge 300 ml	Bag 400 ml	Bag 600 ml
 Silikon SL milchig transparent	204-002	204-201	204-304
 Silikon SL perlweiß	204-003	204-202	204-305
 Silikon SL pergamon altweiß	204-010	*/**	*/**
 Silikon SL flanel grau	204-011	*/**	*/**
 Silikon SL grau	204-004	*/**	*/**
 Silikon SL anthrazit grau	204-007	*/**	204-303
 Silikon SL anthrazit	204-012	*/**	*/**
 Silikon SL schwarz	204-006	*/**	204-306
 Silikon SL cremeweiß RAL 9001	204-008	*/**	204-307
 Silikon SL grauweiß RAL 9002	204-009	*/**	204-308
 Silikon SL rot braun	204-005	*/**	*/**

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
*Not in stock | **Product on request

Silikon HT

temperature resistant silicone up to +280 °C

- acetate-crosslinking silicone sealant
- for heat-stressed joints, such as in areas of cast iron boilers, fireplaces and tiled stoves
- suitable for ceramics and similar materials
- for joints between non-corrodible metals, e.g. as a „liquid“ seal in engine constructions
- for interior and exterior use
- temperature resistant up to +280 °C
- highly elastic, resistant to chemicals and ageing

Order designation	Cartridge 300 ml
 Silikon HT rotbraun	207-001
 Silikon HT schwarz	207-006

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



Profi Neutralsilikon 25

high quality, neutral-crosslinking silicone sealant

- sealant for interior and exterior areas
- for joints even in difficult areas, such as wet areas, swimming pools and pool surroundings, natural and artificial stones, floors and other expansion joints
- suitable for gluing mirrors
- suitable for countless building materials
- anti-mold-tested according to ISO 846
- high volume stability during curing
- high elasticity 25LM
- temperature resistant up to +180 °C
- tested food compability
- very good resilience
- not corrosive to metals
- UV and aging resistant
- stable
- good smoothing properties
- waterproof
- solvent and phthalate free
- very low emission – EMICODE EC1^{PLUS}
- NO MEKO – no butanone oxime is produced during processing
- Class A+ according to French VOC emissions regulations

Order designation	Cartridge 300 ml	Alubeutel 400 ml	Alubeutel 600 ml
Profi Neutralsilikon 25 milchig-transparent	207-071	* / **	207-413
Profi Neutralsilikon 25 perlweiß	207-070	* / **	207-410
Profi Neutralsilikon 25 pergamon altweiß	207-087	* / **	* / **
Profi Neutralsilikon 25 fugen grau	207-090	* / **	* / **
Profi Neutralsilikon 25 manhattan	207-089	* / **	* / **
Profi Neutralsilikon 25 grau weiß	207-077	* / **	* / **
Profi Neutralsilikon 25 silber grau	207-079	* / **	* / **
Profi Neutralsilikon 25 stein grau	207-081	* / **	207-416
Profi Neutralsilikon 25 grau	207-073	* / **	* / **
Profi Neutralsilikon 25 eisen grau	207-084	* / **	207-415
Profi Neutralsilikon 25 beton grau	207-082	* / **	207-414
Profi Neutralsilikon 25 stahl grau	207-091	* / **	* / **
Profi Neutralsilikon 25 seiden grau	207-083	* / **	207-412
Profi Neutralsilikon 25 sanitär grau	207-080	207-380	207-411
Profi Neutralsilikon 25 anthrazit	207-085	* / **	* / **
Profi Neutralsilikon 25 schwarz	207-076	* / **	* / **
Profi Neutralsilikon 25 jasmin cremeweiß	207-078	* / **	* / **
Profi Neutralsilikon 25 bahama beige	207-074	* / **	* / **
Profi Neutralsilikon 25 wüsten beige	207-088	* / **	* / **
Profi Neutralsilikon 25 bali dunkelbraun	207-086	* / **	* / **
Profi Neutralsilikon 25 aluminium	207-093	* / **	* / **

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
*Not in stock | **Product on request



Universalsilikon + Stein

versatile neutral-crosslinking silicone sealant, e.g. for artificial and natural stone

- sealant for interior and exterior areas
- for joints even in difficult areas, such as wet areas, swimming pools and pool surroundings, natural and artificial stones, floors and other expansion joints
- suitable for gluing mirrors
- suitable for countless building materials
- anti-mold-tested according to ISO 846
- high volume stability during curing
- high elasticity 20LM
- temperature resistant up to +180 °C
- tested food compability
- very good resilience
- not corrosive to metals
- UV and aging resistant
- stable
- good smoothing properties
- waterproof
- solvent and phthalate free
- very low emission – EMICODE EC1
- NO MEKO – no butanone oxime is produced during processing

Order designation	Cartridge 300 ml	Alubeutel 600 ml
Universalsilikon+Stein milchig-transparent	207-021	* / **
Universalsilikon + Stein weiß	207-020	207-420
Universalsilikon + Stein bahama	207-024	* / **
Universalsilikon + Stein dark manhattan	207-022	* / **
Universalsilikon + Stein grau	207-023	207-423
Universalsilikon + Stein anthrazit	207-025	* / **
Universalsilikon + Stein schwarz	207-026	* / **

Packing unit: 12 cartridges/box or 20 aluminium bags/box, 1.248 cartridges/pallet
*Not in stock | **Product on request | Bags (400 ml) on request



Universalsilikon matt

particularly high-quality, neutral-crosslinking, structured surface

- matte and lightly textured surface
- for joints in indoor and outdoor areas, e.g. kitchens, bathrooms, pool trims, natural and artificial stones, floors and other expansion joints
- UV and aging resistant
- stable
- good smoothing properties
- solvent and phthalate free
- very low emission – EMICODE EC1^{PLUS}
- NO MEKO – no butanone oxime is produced during processing

Order designation	Cartridge 300 ml
Universalsilikon perlweiß matt	207-036
Universalsilikon perlbeige matt	207-029
Universalsilikon hellgrau matt	207-035
Universalsilikon mittelgrau matt	207-027
Universalsilikon felsgrau matt	207-028
Universalsilikon zementgrau matt	207-033
Universalsilikon schiefergrau matt	207-034
Universalsilikon schwarz matt	207-037



Packing unit: 12 cartridges/box, 1.248 cartridges/pallet
Bags (400 and 600 ml) on request



Silikon SF

neutral cross-linking, highly elastic silicone sealant

- neutrally crosslinking silicone sealant
- for sealing building expansion joints
- suitable for inner connection joints at window mountings according to ÖNORM B 5320
- excellent adhesion to glass, metal, concrete, clinker and many plastics
- UV and ageing resistant
- highest elasticity according to EN 15651-1: Class 25LM
- application as fire protection silicone, e.g. for fire protection windows, doors and gates. Important: follow the installation instructions of the element manufacturer
- flame retardant – B1 according to DIN 4102-1
- NO MEKO – no butanone oxime is produced during processing

Order designation	Cartridge 300 ml
 Silikon SF weiß	207-004
 Silikon SF grau	207-002

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
Bags (400 and 600 ml) on request

Silikon N-Basic

construction silicone

- neutrally crosslinking silicone
- for joints in indoor and outdoor areas
- elongation at break: 250% according to EN 8339
- temperature resistant up to +160 °C
- UV and ageing resistant
- NO MEKO – no butanone oxime is produced during processing

Order designation	Cartridge 300 ml	Alubeutel 600 ml
 Silikon N-Basic transparent	206-101	206-310
 Silikon N-Basic weiß	206-102	* / **
 Silikon N-Basic grau	206-107	* / **

Packing unit: 20 cartridges or aluminium bags/box, 1.200 cartridges/pallet
*Not in stock | **Product on request

Schalungssilikon

special silicone for formwork panels

- neutrally crosslinking silicone sealant for sealing and filling joints in formwork panels
- suitable for repairing silicon joints of formwork panels
- very good adhesion on galvanized metal frames
- temperature resistant up to +180 °C
- very high abrasion resistance
- fast curing
- UV and ageing resistant
- very good smoothing properties
- particularly durable
- permanently elastic
- waterproof
- NO MEKO – no butanone oxime is produced during processing

Order designation	Cartridge 300 ml	Alubeutel 600 ml	Fass ca. 200 l
 Schalungssilikon grau	203-701	203-705	203-700











Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
Bags (400 ml) on request



MS PowerFlex 25

sealant with excellent adhesion on countless materials

- high quality sealant and adhesive based on hybrid polymers
- for bonding and sealing a wide variety of materials; ideal for home, garden, industry, construction and craft
- for concrete, masonry, plaster, wood, metals and plastic
- for connection and movement joints in indoor and outdoor areas, especially suitable for joints in building construction
- suitable for sealing the interior and exterior window connection joint according to ÖNORM B 5320
- very good adhesion even on damp surfaces
- highest elasticity
- anti-mold-tested according to ISO 846
- normally flammable according to EN 13501
- permissible permanent joint movement 25%
- tested food compatibility
- UV and ageing resistant
- good smoothing properties
- neutrally crosslinking
- paintable
- highly elastic
- solvent-free
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)
- very low emission – EMI CODE EC1^{PLUS}

Order designation	Cartridge 290 ml	Alubeutel 600 ml
 MS PowerFlex 25 weiß	209-069	209-301
 MS PowerFlex 25 licht grau	* / **	* / **
 MS PowerFlex 25 grau	209-070	209-302
 PowerFlex 25 mittelgrau	* / **	* / **
 MS Powerflex 25 Mörtel grau	* / **	209-303
 MS Powerflex 25 beton grau	* / **	209-304
 MS Powerflex 25 kieselgrau	* / **	* / **
 MS Powerflex 25 basalt dunkelgrau	* / **	* / **
 MS Powerflex 25 grau braun	209-071	* / **
 MS Powerflex 25 schwarz	209-072	* / **

Packing unit: 12 cartridges/box or 20 aluminium bags/box, 1.248 cartridges/pallet
*Not in stock | **Product on request | Bags (400 ml) on request



MS Putzstruktur

with a plaster-like structure

NEW
PRODUCT

- high-quality structured sealant based on hybrid polymers.
- for the almost invisible connection to plastered surfaces such as e.g., the outer window connection
- suitable for sealing the inner and outer window connection according to ÖNORM B 5320 for concrete, masonry, plaster, wood, metals, and plastic
- for connection and expansion joints indoors and outdoors, especially for joints in building construction
- very good adhesion even on damp substrates
- normally flammable according to EN 13501
- permissible permanent joint movement: 25%
- UV and ageing resistant
- good smoothing properties
- neutral cross-linking
- can be painted over
- highly elastic
- solvent-free
- fulfills the requirements for ecological building materials (does not contain phthalates, halogen compounds, flame retardants, etc.)
- very low emission - EMICODE EC1^{PLUS}



Order designation

Cartridge 290 ml
Alubeutel 600 ml

MS Putzstruktur weiß 209-005 209-006

Packing unit: 20 cartridges or aluminium bags/box, 1.200 cartridges/pallet
Bags (400 ml) on request

MS Hybrid

particularly versatile sealant and adhesive

- sealant and adhesive based on hybrid polymers
- for bonding and sealing a wide variety of materials; ideal for home, garden, industry, construction and craft
- for concrete, natural stone, masonry, plaster, wood, metals and plastic
- for connection and movement joints in indoor and outdoor areas, especially for joints in building construction
- very good elasticity
- permissible permanent joint movement 20%
- tested food compatibility
- UV and ageing resistant
- very good smoothing properties
- neutrally curing
- paintable
- solvent-free
- highly elastic
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)
- very low emission - EMICODE EC1^{PLUS}

Order designation

Cartridge 290 ml

MS Hybrid weiß	209-096
MS Hybrid manhattan	209-102
MS Hybrid dark manhattan	209-104
MS Hybrid steingrau	209-103
MS Hybrid grau	209-097
MS Hybrid schwarz	209-098

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
Bags (400 and 600 ml) on request



MS Transparent

transparent sealant based on hybrid polymers

- for bonding and sealing a wide variety of materials; for home, industry, construction and crafts
- for concrete, masonry, plaster, wood, metals and plastic
- for joints in the interior
- good adhesion even on slightly damp surfaces
- easy processing
- not corrosive to metals
- high volume stability during curing
- ageing-resistant
- stretchable
- neutrally curing
- paintable
- contains no phthalates, halogen compounds, flame retardants, etc.

Order designation

Cartridge 290 ml

MS Transparent	209-077
----------------	---------

Packing unit: 12 cartridges/box, 1.248 cartridges/pallet
Bags (400 and 600 ml) on request



Acrylat D

particularly elastic acrylic sealant

- odorless acrylic dispersion sealant
- suitable for sealings in interior and facade areas on absorbent building materials, such as plaster, concrete, wood and masonry
- suitable for inner connection joints at window mountings according to ÖNORM B 5320
- processable on damp substrates
- for interior and exterior use
- very good elasticity
- paintable
- can be easily plastered over
- can be used with a spatula
- water soluble in fresh condition - easy cleaning of tools
- protect against permanent standing water
- protect against rain during processing and drying time
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)
- very low emission – EMICODE EC1^{PLUS}

Order designation	Cartridge 300 ml	Alubeutel 400 ml	Alubeutel 600 ml
Acrylat D 300 ml weiß	208-003	208-203	208-303
Acrylat D 300 ml grau	208-007	* / **	* / **
Acrylat D 300 ml braun	208-015	* / **	* / **

Packing unit: 20 cartridges or aluminium bags/box, 1.200 cartridges/pallet
*Not in stock | **Product on request



Maleracryl

outstanding smoothable acrylic sealant

- acrylic dispersion sealant for joints and cracks in walls and ceilings
- also suitable for many plastics and for corrosion-protected metals, such as aluminum
- for absorbent building materials such as plaster, concrete, brick, aerated concrete, plasterboard, masonry, wood and fiber cement
- processable on damp substrates
- paintable
- particularly soft and therefore particularly good smoothing properties
- protect against permanent standing water
- protect against rain during processing and curing time
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)
- very low emission – EMICODE EC1^{PLUS}

Order designation	Cartridge 300 ml
Maleracryl 300 ml weiß	208-110

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
Bags (400 and 600 ml) on request



Acrylat AC

paintable and ready to use acrylic sealant

- acrylic dispersion sealant
- suitable for filling joints, cracks and outbreaks with little movement
- suitable for connection joints with little movement
- for absorbent building materials such as plaster, concrete, masonry and wood
- for interior and exterior use
- stretchable
- protect against permanent standing water
- protect against rain during processing and curing time
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)

Order designation	Cartridge 300 ml	Alubeutel 400 ml	Alubeutel 600 ml
Acrylat AC 300 ml weiß	208-103	208-403	208-503
Acrylat AC 300 ml grau	208-107	* / **	* / **

Packing unit: 20 cartridges or aluminium bags/box, 1.200 cartridges/pallet
*Not in stock | **Product on request



Acrylat Basic

paintable filling compound

- for filling of cracks, holes and joints
- suitable for brick, concrete and plaster
- ready to use
- processable on damp substrates
- for interior and exterior use
- paintable
- can be easily plastered over
- can be used with a spatula
- water soluble in fresh condition - easy cleaning of tools
- protect against permanent standing water
- protect against rain during processing and drying time
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)

Order designation	Cartridge 300 ml
Acrylat Basic 300 ml weiß	208-024
Acrylat Basic 300 ml grau	208-025

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
Bags (400 and 600 ml) on request



Acrylat RF

with plaster structure

- ready-to-use smoothing compound
- for repairing cracks in masonry and plaster
- for repair works on facades
- for filling unevennesses
- for interior and exterior use
- protect against permanent standing water
- protect against rain during processing and curing time
- solvent-free
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)

Order designation	Cartridge 300 ml
<input type="checkbox"/> Acrylat RF weiß	218-003

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
Bags (400 and 600 ml) on request



Parkettfugenmasse

solvent-free acrylic sealant for parquet floors

- sealant for connection joints and repairs in parquet and laminate floors as well as skirting boards
- for repairing defects in wooden doors, stairs and furniture
- balances minor movements
- paintable
- ready to use
- silicone-free
- odorless
- water soluble in fresh condition - easy cleaning of tools
- protect against permanent standing water
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)

Order designation	Cartridge 300 ml
<input type="checkbox"/> Parkettfugenmasse buche	211-001
<input type="checkbox"/> Parkettfugenmasse esche/fichte	211-002
<input type="checkbox"/> Parkettfugenmasse eiche	211-003
<input type="checkbox"/> Parkettfugenmasse ahorn	211-006

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
Bags (400 and 600 ml) on request



Acrylat SF

hardly inflammable acrylic sealant

- acrylic dispersion sealant
- for fire-retardant components, such as windows and doors, according to element manufacturer specifications
- particularly suitable for grouting fire protection panels in interior work
- good adhesion on fire protection foam as well as absorbent building materials such as plaster, concrete, masonry, etc.
- flame retardant – B1 according to DIN 4102-1
- „non-burning droplets“ according to DIN 4102-16
- paintable
- protect against permanent standing water
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)

Order designation	Cartridge 300 ml
<input type="checkbox"/> Acrylat SF 300 ml weiß	208-803
<input type="checkbox"/> Acrylat SF 300 ml grau	208-807

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet
Bags (400 and 600 ml) on request



Spenglermasse

processable on damp substrates

- elastic, silicone-free synthetic rubber
- very good adhesion on most surfaces
- suitable for facade, glass, sanitary, ventilation and roof areas
- bitumen-compatible
- for interior and exterior use
- very good moisture resistance
- UV-resistant
- Weather resistant
- paintable with most paints
- contains solvents

Order designation Cartridge
300 ml

Spenglermasse 300 ml 209-009

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



Glättmittel

perfect joints in a few easy steps

- significantly better smoothing properties of sealants
- ready to use mixture
- suitable for silicone and MS-hybrid sealants and adhesives
- prevents sealant damages that can occur when smoothing with detergent mixtures
- application:
 1. Insert sealants into joints, overfilling slightly.
 2. Spray joint with smoothing agent.
 3. Cover removal aid (spatula, stick, etc.) in smoothing agent.
 4. Repeat step 2 & 3 as needed until the joint is smooth.

Order designation Spray bottle
450ml Canister
5l

Glättmittel 450 ml 305-001 305-100

Packaging unit: 6 spray bottles/box, 2 canister/box



Grundierung OP

primer for silicones and MS sealants on porous substrates

- primer for porous, absorbent substrates
- for porous, absorbent, neutral and alkaline substrates, such as concrete, aerated concrete, bricks, fiber cement as well as artificial and natural stones
- apply a thin layer with a brush and let dry
- as a bonding agent it ensures improved adhesion of the sealant, especially on difficult substrates
- contains solvents
- flash off time: approx. 30 minutes
- only for professional and industrial use (not for private users)

Order designation Can
400 ml

Grundierung OP 212-021

Packaging unit: 12 cans/box



Clipdüsen für Kartuschen 5 Stk. SB-Packung

replacement nozzles for all INSEBO® adhesives and sealants

- 3 pcs. cartridge tips for silicones, acrylates and other sealants
- 2 pcs. with cap
- suitable for all INSEBO® cartridges

Order designation Package
5 Stk

Clipdüsen für Kartuschen 213-033



Grundierung GP

primer for silicones and MS sealants on closed-pored substrates

- primer for non-absorbent substrates
- suitable for metals, coatings (such as glazes), for facade paints and plastics (such as acrylic glass, polycarbonate and polyester)
- apply a thin layer with a brush and let dry
- as a bonding agent it ensures improved adhesion of the sealant, especially on difficult substrates
- contains solvents
- flash off time: approx. 30 minutes
- only for professional and industrial use (not for private users)

Order designation Can
400 ml

Grundierung GP 212-022

Packaging unit: 12 cans/box



Spezialdüsen-Set SB-Packung

nozzle set for hard-to-reach areas

- 360° nozzle: for angled corners
- spreader nozzle 30 mm: for extensive applications
- nozzle extension: for deep, inaccessible areas
- v-seam nozzle: for a V-shaped sealing or adhesive bead

Order designation Package
SB

Spezialdüsen-Set 213-034



Flächendüse

quick and clean surface bonding

- 300mm long surface nozzle without pre-drilled holes
- hole spacing (specified grid) and hole diameter (between 2 to 5mm) can be determined and drilled independently
- for a variety of application possibilities

Order designation	Package 10 Stk.
Flächendüse 300mm	213-037

NEW
PRODUCT



Verbindungsstück für Alubeutel

connecting piece between aluminum bag and surface nozzle

- connecting piece between aluminum bag and surface nozzle
- suitable for most aluminum bag presses
- simple click system

Order designation	Package 10 Stk.
Adapterdüse Alubeutel	213-036

NEW
PRODUCT



Verbindungsstück für Kartuschen

connecting piece between cartridge and surface nozzle

- connecting piece between cartridge and surface nozzle
- suitable for all commercially available cartridges (290 ml, 300 ml, and 310 ml)
- screw thread for connecting the cartridge
- simple click system

Order designation	Package 10 Stk.
Adapterdüse Kartusche	213-035

NEW
PRODUCT



Statikmischer

suitable for the 2K Anker Fix

- mixing nozzle for the careful blending of the two components of the 2K Anker Fix

Order designation	Package 10 Stk.
Statikmischer 2K Anker Fix	213-038



PE-Rundschnüre

PE round cord - closed-cell structure prevents water absorption


- especially in building waterproofing to avoid triple-flank adhesion
- due to the neutral properties also applicable to absorbent materials
- compatible with all sealants
- complies with DIN 18540 for expansion joint design
- elastic
- flexible
- resistant to aging



Item no.	Order designation	Diameter	Box contents
410-009	PE-Rundschnur 6 mm SB-Packung	6 mm	10 rm
410-001	PE-Rundschnur 6 mm Kleinpackung	6 mm	100 rm
410-015	PE-Rundschnur 6 mm 2.500 rm	6 mm	2.500 rm
410-010	PE-Rundschnur 8 mm SB-Packung	8 mm	10 rm
410-002	PE-Rundschnur 8 mm Kleinpackung	8 mm	100 rm
410-016	PE-Rundschnur 8 mm 1.500 rm	8 mm	1.500 rm
410-011	PE-Rundschnur 10 mm SB-Packung	10 mm	5 rm
410-003	PE-Rundschnur 10 mm Kleinpackung	10 mm	100 rm
410-017	PE-Rundschnur 10 mm 1.150 rm	10 mm	1.150 rm
410-012	PE-Rundschnur 15 mm SB-Packung	15 mm	5 rm
410-004	PE-Rundschnur 15 mm Kleinpackung	15 mm	100 rm
410-018	PE-Rundschnur 15 mm 550 rm	15 mm	550 rm
410-013	PE-Rundschnur 20 mm SB-Packung	20 mm	5 rm
410-005	PE-Rundschnur 20 mm Kleinpackung	20 mm	50 rm
410-019	PE-Rundschnur 20 mm 350 rm	20 mm	350 rm
410-014	PE-Rundschnur 25 mm SB-Packung	25 mm	5 rm
410-006	PE-Rundschnur 25 mm Kleinpackung	25 mm	50 rm
410-020	PE-Rundschnur 25 mm 200 rm	25 mm	200 rm
410-007	PE-Rundschnur 30 mm Kleinpackung	30 mm	25 rm
410-021	PE-Rundschnur 30 mm 160 rm	30 mm	160 rm
410-022	PE-Rundschnur 40 mm 270 rm	40 mm	270 rm
410-023	PE-Rundschnur 50 mm 180 rm	50 mm	180 rm

Drahtaufsteller

stand-up display for sealing compounds filled in cartridges



- especially for cartridges
- stable cartridge dispenser made of wire
- holds 64 cartridges (8 rows of 8 each)
- overall dimensions
width: 47 cm
height: 44 cm
depth: 31 cm
- protective strip on the front to prevent unintentional slipping out of the cartridges

Item number Order designation

801-003 Drahtaufsteller

Kartuschendispenser 5x5

for the presentation of sealants and adhesives filled in cartridges



- especially for cartridges with filling capacity up to 310 ml
- stable cartridge dispenser made of plastic
- holds 25 cartridges (5 rows of 5 each)
- overall dimensions
width: 31 cm
length: 31 cm
height: 4 cm
- company neutral design without logo

Item number Order designation

801-002 Kartuschendispenser 5x5

Kartuschendispenser 8x6

for the presentation of sealants and adhesives filled in cartridges



- especially for cartridges with filling capacity up to 310 ml
- stable cartridge dispenser made of plastic
- holds 48 cartridges (8 rows of 6 each)
- overall dimensions
width: 49 cm
length: 37 cm
height: 4 cm
- with INSEBO® logo on one side

Item number Order designation

801-016 Kartuschendispenser 8x6

PRODUCT OVERVIEW

ADHESIVES

To make sure that everything holds, as it should: bonding and sealing with INSEBO®.

INSEBO® adhesives are constantly being developed. They are made for everyday use, for application on a wide range of surfaces and suitable for many materials and applications.

- 34 PU-Kleber Spezial
- 34 PU-Kleber Power
- 35 Montagekleber TK
- 35 Montagekleber Spezial
- 36 Montagekleber Tempo
- 36 Dichtkleber F
- 37 EPDM Folienkleber MS **NEW!**
- 37 MS Kleber
- 38 MS Kleber Tempo
- 38 2K MS BondX **NEW!**
- 39 2K Anker Fix **NEW!**
- 39 2K Silikon BondX **NEW!**

For more information about our products and the correct application please observe our technical and safety data sheets which you can read and download conveniently on our website (insebo.com).

PU-Kleber Spezial

highest adhesive power for wood, concrete, masonry, plastic and metal

- 1-component polyurethane adhesive that reacts with humidity
- excellent adhesive power
- for absorbent and non-absorbent surfaces, inside and outside, e.g. wood, stone, ceramics, concrete, bricks, many plastics and various metals
- for rigid and extremely strong adhesive joints
- Fills and bridges uneven surfaces and irregularities
- water resistant
- paintable
- color: white

Order designation

Cartridge
300 ml

PU-Kleber Spezial 300 ml

210-011

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



Montagekleber TK

versatile, solvent-free building adhesive

- solvent-free, stable, water-based dispersion adhesive
- for bonding tiles, polystyrene, wood panels, baseboards, window sills, foams, etc. on brick, concrete, plaster, mortar and wood
- high breaking load (10 kg/cm²)
- the adhesive surface must be absorbent
- adhesive layer thickness: at least 2 mm
- UV and ageing resistant
- paintable
- also suitable as filler for cracks and holes in masonry
- color: off-white
- the substrate should be dry, otherwise the drying time is significantly extended
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)

Order designation

Cartridge
300 ml

Bucket
5 kg

Bucket
12 kg

Montagekleber TK 300 ml

210-001

210-003

210-004

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



PU-Kleber Power

waterproof, high-strength and volume-resistant PU adhesive

- moisture-reactive, volume stable, 1-component polyurethane adhesive
- excellent adhesive power
- for absorbent and non-absorbent surfaces, inside and outside, e.g. wood, stone, tiles, concrete, plaster, stoneware, natural stone, cable ducts, clinker, bricks, polystyrene, many plastics and various metals
- for bondings in wall areas and where short-term fixing is not possible e.g. bondings of wooden steps on concrete.
- rigid and extremely strong adhesive bond
- paintable
- color: yellowish

Order designation

Cartridge
300 ml

PU-Kleber Power

210-046

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



Montagekleber Spezial

versatile building adhesive with particularly good adhesion

- solvent-free construction adhesive with high adhesive power
- suitable for materials such as wood, stone, plastic, corrosion-protected sheet metal, aluminum, ceramic tiles, foam boards, etc.
- suitable for claddings, baseboards, plastic-coated wall panels, etc.
- adheres to absorbent and non-absorbent surfaces
- at least one adhesive surface should be absorbent
- UV and ageing resistant
- paintable
- color: white
- the substrate should be dry, otherwise the drying time is significantly extended.
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)

Order designation

Cartridge
300 ml

Montagekleber Spezial 300 ml

210-005

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



Montagekleber Tempo

versatile building adhesive with high bond strength from the beginning

- elastic, solvent-free dispersion adhesive with particularly high initial adhesion
- for bonding tiles, polystyrene, wood panels, baseboards, window sills, corrosion-protected metals, foams, etc. on bricks, concrete, plaster, mortar and wood
- particularly suitable for applications where forces can occur very quickly
- remains correctable for a short time
- excellent adhesion on many substrates
- at least one adhesive surface should be absorbent
- adhesive strength of approx. 1.3 N/mm² already after 5 minutes on a dry, absorbent substrate
- UV and ageing resistant
- paintable
- color: white
- the substrate should be dry, otherwise the drying time is significantly extended.
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)

Order designation

Cartridge
300 ml

Montagekleber Tempo 300 ml

210-071

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



NEW
PRODUCT

EPDM Folienkleber MS

very good adhesion to a wide range of EPDM films

- suitable for sealing and bonding most foil tapes in the field of window and facade construction
- bonding and sealing with the same product
- very high adhesive strength
- good adhesion even on non-absorbent substrates
- very low emission – EMI CODE EC1^{PLUS}
- can also be applied at low temperatures, down to -10 °C
- for airtight and rainproof sealing of window connection foils, and for sealing the trade hole in the corner area of the window sill
- suitable for indoor and outdoor use
- non-corrosive to metals
- UV and age-resistant
- can be painted over or Ready to use
- waterproof
- solvent-free
- color: white

Order designation

Bag
600 ml

EPDM Folienkleber MS

209-615

Packing unit: 20 aluminium bags/box, 1.200 aluminium bags/pallet



Dichtkleber F

adhesive with good initial adhesion to vapor breaks and wind barriers

- special adhesive for airtight connections of foils and fleece on masonry in the interior construction according to DIN 4108-7
- bonding of vapor brake lanes in attic floor extensions
- for bonding and sealing foil tapes, in particular overlaps and folds
- for air-tight and impact-proof sealing of window connection foils as well as for sealing the hole in the windowsill corner area
- excellent adhesion to polyolefins, e.g. films made from polyethylene (PE) and polypropylene (PP)
- easy processing - no adhesive stringing
- no pressure bars required
- high temperature resistance
- processable from -5 °C
- solvent-free
- color: fresh – light blue, dried – grey blue
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)
- very low emission – EMI CODE EC1^{PLUS}

Order designation

Cartridge
300 ml

Bag
600 ml

Dichtkleber F hellblau

210-034

210-033

Packing unit: 20 cartridges or aluminium bags/box, 1.200 cartridges/pallet



MS Kleber

high-quality adhesive based on hybrid polymers

- for elastic bonding in building, car-body, vehicle, caravan and container construction
- for absorbent and non-absorbent surfaces, inside and outside, e.g. wood, stone, tiles, concrete, plaster, stone-ware, natural stone, glass mosaic, cable ducts, clinker, brick, polystyrene, many plastics and various metals
- suitable for gluing mirrors
- particularly high breaking load (>20 kg / cm²)
- good UV and weather resistance
- vibration dampening
- paintable
- odorless
- permanently elastic
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)

Order designation

Cartridge
290 ml

MS Kleber weiß

209-200

MS Kleber grau

209-201

MS Kleber schwarz

209-202

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



MS Kleber Tempo

particularly stable – high initial adhesion – High Tack

- for elastic bonding in building, car-body, vehicle, caravan and container construction
- for absorbent and non-absorbent surfaces, inside and outside, e.g. wood, stone, tiles, concrete, plaster, stoneware, natural stone, glass mosaic, cable ducts, clinker, brick, polystyrene, many plastics and various metals
- suitable for gluing mirrors
- particularly high breaking load (22 kg/cm²)
- high initial adhesion due to exceptional stability
- easy to use: simply apply, press on, release
- In many cases, no temporary fixation necessary
- reaches final strength after complete reaction
- practical V-seam nozzle for precise dosing
- good UV and weather resistance
- vibration dampening
- paintable
- odorless
- permanently elastic
- color: white
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)

Order designation

Cartridge
290 ml

MS Kleber Tempo weiß

209-400

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



2K MS BondX

high-quality 2-component adhesive for demanding applications

- especially for bonding in areas without sufficient humidity
- for elastic bonding in building, caravan, and container construction, floor coverings and skirting boards, cladding, and sandwich components
- for absorbent and non-absorbent substrates, indoors and outdoors, e.g., Wood, stone, tiles, concrete, plaster, glass mosaic, cable ducts, clinker, brick, polystyrene, many plastics, and various metals
- for bonding mirrors
- shock and vibration absorbing
- resistant to weathering and aging.
- can be painted and plastered over
- low odor
- practical standard cartridge
- color: black

Order designation

Cartridge
250 ml

2K MS BondX schwarz

209-215

Packing unit: 12 cartridges/box, 1.248 cartridges/pallet



NEW
PRODUCT

2K Anker Fix

high-quality 2-component adhesive for demanding rigid joints

- tested according to EAD-330499: for cracked and non-cracked concrete
- Tested according to EAD-330087: for post-installed reinforcement connection
- Seismic qualification according to EOTA Technical Report TR049: Seismic Category C1 and C2
- suitable for water-submerged boreholes
- particularly fast reaction time
- suitable for overhead use
- very high load capacities
- high chemical resistance
- waterproof
- including two static mixers per cartridge
- very low emission – EMICODE EC1^{PLUS}

Order designation

Cartridge
300 ml

2K Anker Fix

210-701

Packing unit: 15 cartridges/box, 960 cartridges/pallet



ETA specifications for preparation and borehole cleaning:

- Select a suitable drill bit according to the dimensions of the part to be fastened and drill at a right angle of 90°.
- Thoroughly clean the drill hole of drilling dust, concrete fragments, oil, grease, and other impurities before injecting the mortar. Use an appropriate pump (or compressed air) and a steel brush. Check the diameter of the steel brush before brushing.
- For compact materials such as concrete/solid stone, cleaning is performed out four times, brushing four times, and blowing out the drill hole four times again.
- For non-compact materials such as perforated bricks, cleaning is performed by blowing out four times, brushing the drill hole twice, and blowing it out again four times

NEW
PRODUCT

2K Silikon BondX

high-quality 2-component adhesive for special requirements

- especially for bonding in areas without sufficient humidity
- fulfills the requirements of DGNB/ÖGNI: Q1 to Q4
- UV-resistant bonding of tempered and insulating glass in metal and timber frame construction
- for bonding claddings, sandwich components, panels, and coverings
- suitable for bonding in the RC2 and RC3 range*
- best suited for structural bonding
- for absorbent and non-absorbent substrates, indoors and outdoors, e.g. Wood, stone, tiles, concrete, plaster, glass mosaic, cable ducts, clinker, brick, polystyrene, many plastics
- gap-bridging
- waterproof
- resistant to weathering and aging
- good mechanical properties
- high-quality side-by-side cartridge
- temperature resistant up to +150 °C
- color: grey

Order designation

Cartridge
490 ml

2K Silikon BondX grau

204-066

Packing unit: 20 cartridges/box, 1.200 cartridges/pallet



*A system test must be successfully completed for the bonding of resistance classes RC2 and RC3

PRODUCT OVERVIEW

PU-FOAMS

**Have you already foamed today?
Our ambitious range of PU foams offers
the right product for every requirement.**

1- or 2-component foams, plastic adapters or dispensing guns: INSEBO® PU foams combine the know-how of many decades with the innovative strength of our in-house development laboratory.

- 42 Pistolenschaum 48
- 42 Pistolenschaum Betongrau
- 43 Volumenschaum 65
- 43 Pistolenschaum Tempo
- 43 Pistolenschaum Basic 42
- 44 All Seasons Pistolenschaum
- 44 Winter-Pistolenschaum
- 45 Pistolenschaum Mega
- 45 Pistolenschaum B2
- 46 Weichzellschaum
- 46 Weichzellschaum B2
- 47 Pistolenschaum LM **NEW!**
- 48 Pistolen-Brunnenschaum
- 48 Dämmplattenkleber
- 49 Fugendichtschaum
- 49 Klebeschaum DS
- 50 Pistolen-Brandschutzschaum
- 50 B1 Füllschaum
- 51 Injektageschaum
- 52 2K Schaum
- 53 2K Tempo
- 53 2K Turbo
- 53 2K Rapidschaum
- 54 Montage- und Füllschaum
- 54 All Seasons Montageschaum
- 55 Montageschaum B2
- 55 Montageschaum Basic
- 55 Fensterschaum
- 56 Montage-Brandschutzschaum
- 56 Brunnenschaum
- 57 PU-Universal-Reiniger
- 57 PU-Schaum-Adapter 5 Stk. SB-Packung

For more information about our products and the correct application please observe our technical and safety data sheets which you can read and download conveniently on our website (insebo.com).

Pistolenschaum 48

noise tested gun foam with high yield

- polyurethane foam for processing with the dispensing gun
- 1-component PU foam with excellent adhesion on conventional building surfaces, such as concrete, masonry, wood, polystyrene, chipboard, insulation materials, metals and many plastics
- perfect for filling cavities in ceilings, walls and floors; for filling joints, e.g. between window or door frames and masonry; for filling conduit slits, wall openings and much more
- very high yield
- especially for professional users
- can be processed at ambient temperatures above 3 °C
- economical in operation
- tested as noise protection foam by the ift Rosenheim; joint sound insulation: 62 dB
- excellent thermal insulation; thermal conductivity: $\lambda = 0,0365 \text{ W/mK}$ according to EN 12667
- dimensionally stable and pressure-free after curing
- skin forming time: approx. 8 to 12 minutes
- cuttable after approx. 20 to 30 minutes
- very low emission – EMICODE EC1^{PLUS}
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- shelf life: 15 months
- color: yellow
- yield: 32 liters free-foamed per 500 ml can
- yield: 48 liters free-foamed per 750 ml can



Item number	Order designation	Content
108-961	Profi Pistolenschaum 32 500 ml*	500 ml can
108-001	Pistolenschaum 48 750 ml	750 ml can
108-900	Profi Pistolenschaum 48 750 ml*	750 ml can
108-021	Pistolenschaum-Set klein (3 x foam, 1 x cleaner, 1 x dispensing gun)	
108-030	Pistolenschaum-Set groß (9 x foam, 1 x cleaner, 1 x dispensing gun)	

*only for professional users - will be delivered without gloves

Pistolenschaum Betongrau

grey gun foam with high yield

- concrete-grey polyurethane foam for application with the dispensing gun
- 1-component PU foam with excellent adhesion on conventional building surfaces
- especially for professional users
- further applications and properties as INSEBO® Pistolenschaum 48
- low post-expansion
- skin forming time: approx. 8 to 12 minutes
- cuttable after approx. 20 to 30 minutes
- very low emission – EMICODE EC1^{PLUS}
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- shelf life: 15 months
- color: grey
- yield: 48 liters free foamed per 750 ml can



Item number	Order designation	Content
108-080	Pistolenschaum Betongrau 750 ml	750 ml can
108-902	Profi Pistolenschaum Betongrau 750 ml*	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves

Volumenschaum 65

more foam content in same can size

- 1-component PU foam with excellent adhesion on conventional building surfaces, such as concrete, masonry, wood, polystyrene, chipboard, insulation materials, metals and many plastics
- tested as noise protection foam
- can be processed at ambient temperatures above 3°C
- skin forming time: approx. 8 to 12 minutes
- cuttable after approx. 25 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: yellow
- yield: 65 liters free foamed per 850 ml can



Item number	Order designation	Content
108-600	Volumenschaum 65 850 ml	850 ml can
108-901	Profi Volumenschaum 65 850 ml*	850 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves

Pistolenschaum Tempo

fast curing gun foam

- very fast reacting gun foam
- tested as noise protection foam by the TU Graz; Joint sound insulation: 58 dB
- dimensionally stable and pressure-free after curing
- skin forming time: approx. 5 to 7 minutes
- cuttable after approx. 15 to 20 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: yellow
- yield: 48 liters free foamed per 750 ml can



Item number	Order designation	Content
108-060	Pistolenschaum Tempo 750 ml	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

Pistolenschaum Basic 42

standard gun foam for filling and insulating

- 1-component PU foam with good adhesion to conventional building substrates such as concrete, masonry, wood, polystyrene, chipboard, insulating materials, metals and many plastics
- dimensionally stable and pressurefree after curing
- skin forming time: approx. 8 to 10 minutes
- cuttable after approx. 25 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- shelf life: 12 months
- color: yellow
- yield: 40 liters free-foamed per 750 ml can



Item number	Order designation	Content
108-002	Pistolenschaum Basic 750 ml	750 ml can
108-930	Profi Pistolenschaum Basic 750 ml*	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves

All Seasons Pistolenschaum

winter gun foam processable from -5 °C ambient temperature

- year-round applicable 1-component PU foam
- top product for applications at low temperatures
- at higher ambient temperatures identical properties as „normal“ gun foam
- tested as noise protection foam by the ift Rosenheim; Joint sound insulation: 63 dB (for 10 and 20 mm joints)
- normally flammable according to EN 13501-1
- skin forming time: approx. 6 to 8 minutes
- cuttable after approx. 20 to 30 minutes
- very low emission – EMICODE EC1^{PLUS}
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- Class A+ according to French VOC emissions regulations
- color: yellow
- yield: 30 liters free foamed per 500 ml can
- yield: 44 liters free foamed per 750 ml can

Item number	Order designation	Content
108-007	All Seasons Pistolenschaum 500 ml	500 ml can
108-952	Profi All Seasons Pistolenschaum 500 ml*	500 ml can
108-010	All Seasons Pistolenschaum 500 ml with PDR	500 ml can
108-953	Profi All Seasons Pistolenschaum 500 ml with PDR*	500 ml can
108-033	All Seasons Pistolenschaum 750 ml	750 ml can
108-933	Profi All Seasons Pistolenschaum 750 ml*	750 ml can
108-020	All Seasons Pistolenschaum 750 ml with PDR	750 ml can
108-951	Profi All Seasons Pistolenschaum 750 ml with PDR*	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves



Pistolenschaum Mega

1-component PU foam with excellent adhesion to conventional building substrates

- particularly high yield
- normally flammable – B2 according to DIN 4102
- tested as noise protection foam
- skin forming time: approx. 6 minutes
- cuttable after approx. 15 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: yellow
- yield: 40 liters free-foamed per 500ml can
- yield: 58 liters free-foamed per 750ml can
- yield: 65 liters free-foamed per 850ml can

Item number	Order designation	Content
108-034	Pistolenschaum Mega40 500 ml with PDR	500 ml can
108-971	Profi Pistolenschaum Mega40 500 ml with PDR*	500 ml can
108-035	Pistolenschaum Mega58 with 750 ml PDR	750 ml can
108-972	Profi Pistolenschaum Mega58 750 ml with PDR*	750 ml can
108-036	Pistolenschaum Mega65 850 ml with PDR	850 ml can
108-973	Profi Pistolenschaum Mega65 850 ml with PDR*	850 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves



Winter-Pistolenschaum

winter gun foam processable from -12 °C ambient temperature

- top product for applications at low temperatures
- best foam quality even at lowest temperatures
- at higher ambient temperatures identical properties as „normal“ gun foam
- fine-pored foam structure
- cuttable after approx. 35 to 45 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: yellow
- yield: 36 liters free foamed per 750 ml can

Item number	Order designation	Content
108-014	Winter-Pistolenschaum 750 ml	750 ml can
108-959	Profi Winter-Pistolenschaum 750 ml *	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves



Pistolenschaum B2

gun foam tested according to DIN 4102

- 1-component PU foam with excellent adhesion to construction substrates
- normally flammable – B2 according to DIN 4102
- tested as noise protection foam; joint sound insulation: 62 dB
- skin forming time: approx. 8 to 10 minutes
- cuttable after approx. 20 to 30 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: yellow
- yield: 40 liters free-foamed per 750 ml can

Item number	Order designation	Content
108-935	Profi Pistolenschaum B2 500 ml with PDR*	500 ml can
108-004	Pistolenschaum B2 750 ml with PDR	750 ml can
108-904	Profi Pistolenschaum B2 750 ml with PDR*	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves



Weichzellschaum

airtight and highly elastic gun foam

- for the insulation of interior roof constructions and for filling cavities and wall openings
- a high degree of elongation and compression capability allows for greater joint movement
- movement capability +/-20 % according to EN 17333-4
- very good adhesion on conventional building substrates such as masonry, concrete and wood on insulation materials, metals and many plastics
- excellent adhesion on wood, fiber cement, aerated concrete, concrete, masonry, plaster, XPS and rigid PVC
- tested as noise protection foam by the ift Rosenheim; joint sound insulation: 63 dB
- excellent thermal insulation; thermal conductivity: $\lambda = 0,0365$ W/mK according to EN 12667
- system tested according to ÖNORM B 5320
- airtight: up to 600 Pa
- tested vapor diffusion behavior
- high elasticity
- skin forming time: approx. 8 to 12 minutes
- cuttable after approx. 15 to 20 minutes
- very low emission – EMICODE EC1^{PLUS}
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: white
- yield: 38 liters free-foamed per 750 ml can



Item number	Order designation	Content
108-317	Weichzellschaum 750 ml	750 ml can
108-921	Profi Weichzellschaum 750 ml*	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves

Weichzellschaum B2

highly elastic and normally flammable according to EN 13501

- for the insulation of interior roof constructions and for filling cavities and wall openings
- a high degree of elongation and compression capability allows for greater joint movement
- movement capability +/-15 % according to EN 17333-4
- very good adhesion on conventional building substrates such as masonry, concrete and wood on insulation materials, metals and many plastics
- excellent adhesion on wood, fiber cement, aerated concrete, concrete, masonry, plaster, XPS and rigid PVC
- normally flammable according to EN 13501
- high elasticity
- skin forming time: approx. 6 to 8 minutes
- cuttable after approx. 15 to 20 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: white
- yield: 32 liters free-foamed per 750 ml can



Item number	Order designation	Content
108-320	Weichzellschaum B2 750 ml	750 ml can
108-942	Profi Weichzellschaum B2 750 ml*	750 ml can
108-321	Weichzellschaum B2 750 ml with PDR	750 ml can
108-947	Profi Weichzellschaum B2 750 ml with PDR*	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves

NEW PRODUCT



Pistolenschaum LM

user-friendly: < 0.1% free isocyanates

- low monomer and low-emission 1C gun foam
- meets the requirements of DGNB: Q1 to Q4
- excellent adhesion to standard building substrates, such as concrete, masonry, wood, polystyrene, chipboard, insulating materials, metals, and many plastics
- for insulation in windows and doors, interior roof finishing, and for foaming out cavities and wall openings
- very high yield
- climate-friendly propellant gases (free from CFCs, HCFCs, and HFCs)
- tested as sound insulation foam by the ift Rosenheim; joint sound insulation: 62 dB
- excellent thermal insulation; Thermal conductivity: $\lambda = 0.0365$ W/mK according to EN 12667
- airtight up to 600 Pa
- tested vapor diffusion behavior
- very low emission – EMICODE EC1^{PLUS}
- shelf life: 18 months
- color: white
- yield: 35 liters of free-foaming per 750 ml can

Item number	Order designation	Content
108-906	Profi Pistolenschaum LM	750 ml can

Packing unit: 12 cans/box, 70 boxes/pallet

Isocyanate training not required



Pistolen-Brunnenschaum

mounting of concrete shaft- and well rings

- processing with dispensing gun
- special foam for installing shaft- and well rings
- tested for water resistance
- resistant to gasoline, oil and water
- skin forming time: approx. 8 to 10 minutes
- cuttable after approx. 20 to 25 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: blue
- yield: 48 liters free-foamed per 750 ml can

Item number	Order designation	Content
108-073	Pistolen-Brunnenschaum 750 ml	750 ml can
108-939	Profi Pistolen-Brunnenschaum 750 ml*	750 ml can
108-097	Pistolen Brunnenschaum 750 ml with PDR	750 ml can
108-974	Profi Pistolen Brunnenschaum 750 ml with PDR*	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves



Fugendichtschaum

foam sealant for rainproof connections in the facade area

- for connection joints in facades, roof windows, partition walls, HVAC (heating/ventilating/air conditioning) systems, etc.
- high adhesive strength on most common building substrates such as masonry, concrete, wood, insulation materials, metals, and many plastics.
- dimensionally stable and dwell-pressure free after curing
- skin forming time: approx. 6 to 8 minutes
- non-sticky after approx. 15 to 20 minutes
- normally flammable according to EN 13501
- driving rain tightness: Joint width 15 mm to 39 mm: 450 Pa Joint width from 40 mm: 600 Pa
- water vapor permeability: $\mu = 12.4$ according to EN 12572
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: blue
- yield: 35 liters free-foamed per 750 ml can

Item number	Order designation	Content
108-037	Fugendichtschaum 750 ml	Dose 750 ml
108-976	Profi Fugendichtschaum 750 ml*	Dose 750 ml

Packing unit: 12 cans/box, 56 boxes/pallet

*nur für gewerbliche Anwender – wird ohne Handschuhe geliefert



Dämmplattenkleber

PU foam adhesive for bonding polystyrene insulation boards

- gun foam for easy fixation of the perimeter insulation
- excellent adhesion on many building substrates
- tested for compatibility with bituminous coatings (PMBC – Polymer Modified Bituminous Coatings)
- high yield – fast-curing
- easy and fast processing
- no preparation time required
- fine-pored cell structure – dimensionally stable
- one can is enough for about 12 to 15 m²
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- shelf life: 15 months
- color: yellow
- yield: 47 liters free-foamed per 750 ml can

Item number	Order designation	Content
108-318	Dämmplattenkleber 750 ml	750 ml can
108-903	Profi Dämmplattenkleber 750 ml*	750 ml can
108-355	Dämmplattenkleber 750 ml with PDR	750 ml can
108-975	Profi Dämmplattenkleber 750 ml with PDR*	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves



Perimeter insulation – step by step



1. Apply foam in strips at intervals of approx. 25 to 30 cm.
2. Press on the insulation board and rub it so the glue can distribute well.
3. Align and support the lowest row of insulation boards and after a few minutes, the second row can already be set up.

Klebschaum DS

certified adhesive foam for ETICS applications

- particularly suitable as an adhesive for perimeter insulation boards
- can only be used within the scope of an ETICS certification in areas requiring approval
- excellent adhesion to conventional building substrates such as concrete, masonry, plaster, wood, chipboard, insulation materials, metals and many plastics
- tested according to TR 46 for technical evaluation for ETICS according to ETAG 004
- „non-burning droplets“ according to DIN 4102-16
- flame retardant – B1 according to DIN 4102-1
- dimensionally stable and dwell-pressure free after curing
- skin forming time: approx. 6 minutes
- non-sticky after approx. 15 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: yellow
- yield: 40 liters free-foamed per 750 ml can

Item number	Order designation	Content
108-316	Klebschaum DS 750 ml	750 ml can
108-342	Klebschaum DS 750 ml with PDR	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet



Pistolen-Brandschutzschaum

flame retardant according to EN 13501 and DIN 4102

- excellent adhesion to conventional building substrates such as concrete, masonry, wood, polystyrene, chipboard, insulation materials, metals and many plastics
- for filling joints, cavities and wall openings
- observe the regulations of the fire protection element manufacturers
- flame retardant – B - s1, d0 according to EN 13501-1
- flame retardant – B1 according to EN 4102-1
- „non-burning droplets“ according to DIN 4102-16
- „allgemein bauaufsichtliches Prüfzeugnis abP“ (general test certificate issued by an approved building inspectorate) for Germany issued by the MPA Hannover
- skin forming time: approx. 8 to 10 minutes
- cuttable after approx. 30 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: yellow
- yield: 40 liters free-foamed per 750 ml can



Item number	Order designation	Content
107-200	Pistolen-Brandschutzschaum 750 ml	750 ml can
107-201	Pistolen-Brandschutzschaum 750 ml with PDR	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

B1 Füllschaum

fine-pored B1 PU foam – hardly inflammable

- for filling narrow joints according to ÖNORM B 6400 in ETICS
- flame retardant gun foam with excellent adhesion to common construction substrates such as concrete, masonry, plaster, wood, chipboard, insulation materials, metals and many plastics
- for filling joints, cavities and wall openings
- flame retardant – B1 according to DIN 4102-1
- dimensionally stable and pressure-free after curing
- skin forming time: approx. 8 to 12 minutes
- cuttable after approx. 30 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- shelf life: 15 months
- color: yellow
- yield: 40 liters free-foamed per 750 ml can



Item number	Order designation	Content
107-221	B1 Füllschaum 750 ml	750 ml can
107-921	Profi B1 Füllschaum 750 ml*	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves

Injektageschaum

for the subsequent refurbishment of WDV systems


- for subsequent bonding of EPS-F insulation boards in already installed thermal insulation composite systems*
- for the subsequent reduction of air circulation between the load-bearing structure and EPS-F insulation boards in already installed thermal insulation composite systems*
- fire behavior according to EN 13501-1: „flame retardant“, Class B - s1, d0
- very good adhesive strength on the most common EPS and XPS insulation boards
- excellent adhesion to concrete, aerated concrete, brick, fiber cement, masonry, and plaster
- easy to rework e.g., cutting, sawing, plastering, and painting over
- quick and easy to work with
- thermally insulating
- harmless when in the hardened state

*Please be sure to observe the instructions in the technical data sheet, specifically in the section "Processing Instructions"

Item number	Order designation	Content
107-950	Profi Injektageschaum**	750 ml can

Packing unit: 12 cans/box, 56 boxes/pallet

*only for professional users - will be delivered without gloves



Schematische Darstellung:


- Bohrloch
- ↔ Raster-Abstand gemäß Planer-Vorgabe

According to the grid spacing specified by the above-mentioned planner, holes are drilled through the insulation board to the supporting structure. The hole diameter should be 1-2mm larger than the outer diameter of the pipe of the used PU foam gun. Subsequently, the hole should be moistened with water using a spray bottle, ensuring sufficient moisture for the subsequently applied injection foam to react optimally. The amount of foam to be applied is specified by the above-mentioned planner for the specific object. Due to varying conditions from object to object, WS INSEBO cannot assume general liability. The ÖNORM B 6400 must be complied with in all cases.

2K Schaum

high resistance and dimensional stability

- 2-component PU foam with high compressive strength
- particular suitability for mounting door frames and window sills
- for filling joints and cavities where it is not possible to supply moisture, such as in boat construction, shower trays, in metal construction, etc.
- high adhesion to most building substrates such as masonry, concrete, wood, insulation materials, metals and many plastics
- excellent adhesion on wood, fiber cement, aerated concrete, concrete, masonry, plaster, XPS and hard PVC
- reacts without adding moisture
- processing time: approx. 8 minutes
- tested as noise protection foam by the Technical University of Graz; joint sound insulation: 61 dB
- dimensionally stable and pressure-free after curing
- cuttable after approx. 20 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: green
- yield: 13 liters free-foamed per 440 ml can
- yield: 18 liters free-foamed per 600 ml can



Item number	Order designation	Content
109-001	2K Schaum 440 ml	440 ml can
109-900	Profi 2K Schaum 440 ml*	440 ml can
109-011	2K Schaum 600 ml	600 ml can
109-911	Profi 2K Schaum 600 ml*	600 ml can

Packing unit: 12 cans/box, 48 boxes/pallet

*only for professional users - will be delivered without gloves

Door frame installation – step by step *



1. Set up the frame and brace it.



2. Foam with 2-component PU foam.



3. After curing, despread and cut off the surplus PU foam.



4. Attach the panel and hinge the door leaf.

*Observe ÖNORM B 5335 and the installation instruction of the door frame manufacturer.

2K Tempo

fast, low-emission 2-component foam

- fast-curing, 2-component PU foam
- for fast mounting of door frames and windowsills
- cuttable after 15 minutes, despreadable after 30 minutes and fully loadable after 90 minutes
- significantly higher strength compared to 1-component PU foams
- reacts without adding moisture
- very low emission
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: green
- yield: 12 liters free-foamed per 400 ml can



Item number	Order designation	Content
110-005	2K Tempo 400 ml	400 ml can
110-900	Profi 2K Tempo 400 ml*	400 ml can

Packing unit: 12 cans/box, 48 boxes/pallet

*only for professional users - will be delivered without gloves

2K Turbo

fast-curing, low emission 2-component foam with fire class E

- fast-curing, 2-component PU foam
- for fast mounting of door frames and windowsills
- cuttable after 15 minutes, despreadable after 30 minutes and fully loadable after 90 minutes
- significantly higher strength compared to 1-component PU foams
- normally flammable according to EN 13501
- reacts without adding moisture
- very low emission
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: green
- yield: 12 liters free-foamed per 400 ml can



Item number	Order designation	Content
110-001	2K Turbo 400 ml	400 ml can
110-903	Profi 2K Turbo 400 ml*	400 ml can
110-010	2K Turbo 400 ml with PDR	400 ml can
110-901	Profi 2K Turbo 400 ml with PDR*	400 ml can

Packing unit: 12 cans/box, 48 boxes/pallet

*only for professional users - will be delivered without gloves

2K Rapidschaum

high strength propellant-free cartridge foam

- 2-component cartridge foam for the application of door frames, filling gaps and assembling prefabricated components
- fast curing – cuttable after 5-10 minutes
- reaches final strength after approx. 20 minutes
- high adhesion
- normally flammable – B2 according to DIN 4102
- easy processing with Doppelpresse FX7-21 DP
- propellant-free
- color: yellow



Item number	Order designation	Content
109-050	2K Rapidschaum	210 ml cartridge
640-005	Doppelpresse FX7-21 DP	

Packing unit: 16 cans/box

*only for professional users - will be delivered without gloves

Montage- und Füllschaum

the universal PU straw foam for do-it-yourselfers and craftsmen

- 1-component PU foam with excellent adhesion to common construction substrates, such as concrete, masonry, wood, polystyrene, chipboard, insulating materials, metals and many plastics
- for filling cavities in ceilings, walls and floors; for filling joints, e.g. between window or door frames and masonry; for filling conduit slits, wall openings and much more
- tested as noise protection foam by the ift Rosenheim; Joint sound insulation: 62 dB
- dimensionally stable and dwell-pressure free after curing
- skin forming time: approx. 8 to 10 minutes
- cuttable after approx. 30 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- shelf life: 15 months
- color: yellow
- yield: 23 liters free-foamed per 500 ml can
- yield: 27 liters free-foamed per 600 ml can
- yield: 34 liters free-foamed per 750 ml can

Item number	Order designation	Content
101-001	Montage- und Füllschaum 500 ml	500 ml can
101-003	Montage- und Füllschaum 600 ml	600 ml can
101-005	Montage- und Füllschaum 750 ml	750 ml can
101-900	Profi Montage- und Füllschaum 750 ml*	750 ml can

Packing unit: 12 cans/box, 48 boxes/pallet

*only for professional users - will be delivered without gloves



All Seasons Montageschaum

winter straw foam processable from -10 °C ambient temperature

- year-round applicable 1-component PU foam
- top product for low temperature processing
- Workable from 0 °C can temperature
- perfect PU foam solution for the winter
- Ideal foaming characteristics - optimum stability
- at higher temperatures identical properties as „normal“ straw foam
- skin forming time: approx. 8 to 14 minutes
- cuttable after approx. 40 to 60 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: yellow
- yield: 32 liters free-foamed per 750 ml can

Item number	Order designation	Content
101-101	All Seasons Montageschaum 750 ml	750 ml can
101-902	Profi All Seasons Montageschaum 750 ml*	750 ml can

Packing unit: 12 cans/box, 48 boxes/pallet

*only for professional users - will be delivered without gloves



Montageschaum B2

the universal PU foam tested according to DIN 4102

- same application and properties as Montage- und Füllschaum
- normally flammable – B2 according to DIN 4102
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: yellow
- yield: 23 liters free-foamed per 500 ml can
- yield: 34 liters free-foamed per 750 ml can

Item number	Order designation	Content
101-004	Montageschaum B2 500 ml with PDR	500 ml can
101-006	Montageschaum B2 750 ml with PDR	750 ml can
101-905	Profi Montageschaum B2 750 ml with PDR*	750 ml can

Packing unit: 12 cans/box, 48 boxes/pallet

*only for professional users - will be delivered without gloves



Profi Montageschaum Basic

one-component PU foam

- 1-component PU foam with good adhesion to common building substrates such as brick, wood, plaster, stone, many insulation materials and various plastics
- dimensionally stable and pressure free after curing
- skin formation time: approx. 8 to 10 minutes
- cuttable after approx. 30 minutes
- environmentally friendly propellants (free of CFCs, HCFCs, and HFCs)
- color: yellow
- yield: 32 litres free foamed per 750 ml can

Item number	Order designation	Content
101-930	Profi Montageschaum Basic*	750 ml can

Packing unit: 12 cans/box, 70 boxes/pallet

*only for professional users - will be delivered without gloves



Fensterschaum

fine-pored PU foam for window installations

- special product for window installations
- easy processing with the foam adapter and yet best foam quality
- 1-component PU foam with excellent adhesion to conventional construction substrates
- high adhesive strength and fast curing
- excellent thermal and acoustic insulation
- skin forming time: approx. 5 to 7 minutes
- cuttable after approx. 25 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: blue
- yield: 36 liters free-foamed per 750 ml can

Item number	Order designation	Content
105-001	Fensterschaum 750 ml	750 ml can

Packing unit: 12 cans/box, 48 boxes/pallet



Montage-Brandschutzschaum

flame retardant according to EN 13501 and DIN 4102

- excellent adhesion to conventional construction substrates such as concrete, masonry, wood, polystyrene, chipboard, insulating materials, metals and many plastics
- for filling joints, cavities and wall openings
- observe the specifications of the fire protection element manufacturer
- flame retardant – B - s1, d0 according to EN 13501-1
- flame retardant – B1 according to DIN 4102-1
- „non-burning droplets“ according to DIN 4102-16
- skin forming time: approx. 8 to 10 minutes
- cuttable after approx. 35 minutes
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- color: yellow
- yield: 32 liters free-foamed per 750 ml can



Item number	Order designation	Content
107-050	Montage-Brandschutzschaum 750 ml	750 ml can
Packing unit: 6 cans/box, 96 boxes/pallet		

PU-Universal-Reiniger

highly effective solvent mixture

- cleaner for removing fresh PU foam inside PU foam guns
- can be used by the spray head as a PU foam cleaner for fresh, not yet cured PU foam
- practical universal cleaner with very good cleaning effect
- with attachable spray head for cleaning soiled surfaces and tools
- highly effective solvent mixture
- shelf life: 18 months



Item number	Order designation	Content
112-015	PU-Universal-Reiniger 500 ml	500 ml spray can
Packing unit: 12 spray cans/box, 84 boxes/pallet		

Brunnenschaum

resistant to water and sewer fluids

- special product for installing shaft- and well rings made of concrete
- resistant to diluted chemicals and mineral oils as well as to water
- climate-friendly propellants (free of CFCs, HCFCs and HFCs)
- shelf life: 15 months
- color: blue
- yield: 36 liters free-foamed per 750 ml can



Item number	Order designation	Content
106-001	Brunnenschaum 750 ml DE-SL-PL	750 ml can
106-003	Brunnenschaum 750 ml DE-SL-PL with PDR	750 ml can
106-900	Profi Brunnenschaum 750 ml DE-SL-PL*	750 ml can
106-903	Profi Brunnenschaum 750 ml DE-SL-PL with PDR*	750 ml can
Packing unit: 12 cans/box, 48 boxes/pallet		

*only for professional users - will be delivered without gloves

PU-Schaumadapter 5 Stk. SB-Packung

replacement tubes for all INSEBO® straw foams

- suitable for INSEBO® straw foams and INSEBO® 2K foams
- 5 pieces per pack
- flexible tube



Item number	Order designation
113-033	PU-Schaumadapter 5 Stk. SB-Packung

PRODUCT OVERVIEW

JOINT SEALING TAPES

Lifelong tapes for windows and doors: Our joint sealing tapes empower you in the battle against noise, wind, and weather.

Whether for windows, facade insulations, or other construction joints, our pre-compressed joint sealing tapes and foil tapes complement our sealing system, withstanding the most demanding conditions.

- 60 Hannoband BG1
- 61 Hannoband BG1-M
- 62 Hannoband 600
- 63 Hannoband BG2
- 64 Hannoband THERM
- 65 Hannoband 3E Basic
- 66 Vorlegeband
- 67 Vorlegeband Extra
- 68 Folienband DUO Easy 240
- 69 Folienband FA Easy Soft 240
- 69 Folienband FI Easy 240
- 70 Anschlussflansch
- 71 Flanschdicht
- 71 Folienprimer

For more information about our products and the correct application please observe our technical and safety data sheets which you can read and download conveniently on our website (insebo.com).

Hannoband BG1

high quality sound insulation and weather protection

Hannoband BG1 is ideally suited for directly and indirectly weathered joints in window construction, in facade areas and in timber construction. The long-lasting recovery properties ensure a permanently tight joint.

- meets the requirements of DIN 18542 (BG1) and ÖNORM B 5320
- driving rain tightness: ≥ 600 Pa
- airtight: $a_n < 1.0$
- vapor-permeable: s_d value ≤ 0.5 m
- joint sound insulation: up to 59 dB
- excellent thermal insulation; thermal conductivity: $\lambda = 0,0412$ W/mK
- flame retardant – B1 according to DIN 4102
- tested for compatibility with adjoining building materials
- temperature resistant from -30 °C to $+100$ °C, for a short time even up to $+130$ °C
- long-term weather-resistant: natural weathering > 15 years
- UV-resistant
- storage stability: 24 months
- very low emission – EMICODE EC1^{PLUS}



Item no.	Order designation	Joint depth	Joint width	Roll length	Rolls per box	Box content
414-001	BG1 10/1,5-2,5	10 mm	1,5-2,5 mm	12 rm	30	360 rm
414-002	BG1 15/1,5-2,5	15 mm	1,5-2,5 mm	12 rm	20	240 rm
414-003	BG1 20/1,5-2,5	20 mm	1,5-2,5 mm	12 rm	15	180 rm
414-004	BG1 10/2-4	10 mm	2-4 mm	10 rm	30	300 rm
414-005	BG1 15/2-4	15 mm	2-4 mm	10 rm	20	200 rm
414-006	BG1 20/2-4	20 mm	2-4 mm	10 rm	15	150 rm
414-007	BG1 10/3-7	10 mm	3-7 mm	7,5 rm	30	225 rm
414-025	BG1 12/3-7	12 mm	3-7 mm	7,5 rm	25	187,5 rm
414-008	BG1 15/3-7	15 mm	3-7 mm	7,5 rm	20	150 rm
414-009	BG1 20/3-7	20 mm	3-7 mm	7,5 rm	15	112,5 rm
414-027	BG1 10/5-10	10 mm	5-10 mm	5 rm	30	150 rm
414-010	BG1 15/5-10	15 mm	5-10 mm	5 rm	20	100 rm
414-011	BG1 20/5-10	20 mm	5-10 mm	5 rm	15	75 rm
414-012	BG1 30/5-10	30 mm	5-10 mm	5 rm	10	50 rm
414-013	BG1 15/7-12	15 mm	7-12 mm	4,3 rm	20	86 rm
414-014	BG1 20/7-12	20 mm	7-12 mm	4,3 rm	15	64,5 rm
414-015	BG1 25/7-12	25 mm	7-12 mm	4,3 rm	12	51,6 rm
414-016	BG1 30/7-12	30 mm	7-12 mm	4,3 rm	10	43 rm
414-017	BG1 20/8-15	20 mm	8-15 mm	3 rm	15	45 rm
414-018	BG1 25/8-15*	25 mm	8-15 mm	3 rm	12	36 rm
414-019	BG1 30/8-15*	30 mm	8-15 mm	3 rm	10	30 rm
414-098	BG1 20/10-18	20 mm	10-18 mm	5 rm	15	75 rm
414-020	BG1 25/10-18	25 mm	10-18 mm	5 rm	12	60 rm
414-410	BG1 SB 15/3-7**	15 mm	3-7 mm	7,5 rm	7	52,5 rm
414-411	BG1 SB 15/5-10**	15 mm	5-10 mm	5 rm	7	35 rm
414-412	BG1 SB 15/7-12**	15 mm	7-12 mm	4,3 rm	7	30,1 rm
414-413	BG1 SB 20/8-15**	20 mm	8-15 mm	3 rm	5	15 rm

Delivery times and other dimensions on request

*Minimum order quantity: 12 boxes or a multiple of this quantity

**These articles are available separately packed and individually labeled

Hannoband BG1-M

highest weather protection and joint tolerance

Hannoband BG1-M completes the product range of Hannoband BG1 for particularly wide joints.

- meets the requirements of DIN 18542 (BG1) and ÖNORM B 5320
- established membrane technology allows higher joint tolerances than conventional sealing tapes
- ideally suited for directly and indirectly weathered joints in window construction, facade and timber constructions
- permanently tight connection thanks to long-lasting recovery properties
- driving rain tightness: ≥ 600 Pa
- airtight: $a_n < 1.0$
- vapor-permeable: s_d - value ≤ 0.5 m
- excellent thermal insulation; thermal conductivity: $\lambda = 0,0429$ W/mK
- flame retardant – B1 according to DIN 4102-1
- very low emission – EMICODE EC1^{PLUS}



Item no.	Order designation	Joint depth	Joint width	Roll length	Rolls per box	Box content
414-442	BG1-M 25 /8-18	25 mm	8-18 mm	4,7 rm	12	56,4 rm
414-441	BG1-M 25/12-25	25 mm	12-25 mm	4,7 rm	12	56,4 rm
414-440	BG1-M 35/20-35	35 mm	20-35 mm	4,7 rm	8	37,6 rm

Delivery times and other dimensions on request

Minimum order quantity: 12 boxes or a multiple of this quantity

Hannoband 600

weather protection for window and facade joints

Hannoband 600 meets the requirements for pre-compressed joint sealing tapes, both for window installation as well as for facade insulation.

- meets the requirements of DIN 18542 (BG1) and ÖNORM B 5320
- driving rain tightness: ≥ 600 Pa
- airtight: $a_n < 1.0$
- vapor-permeable: s_d value ≤ 0.5 m
- excellent thermal insulation; thermal conductivity: $\lambda = 0.0412$ W / mK
- flame retardant – B1 according to DIN 4102
- temperature resistant: from -30 °C to $+100$ °C
- long-term weather-resistant
- UV-resistant
- very low emission – EMI CODE EC1^{PLUS}



Item no.	Order designation	Joint depth	Joint width	Roll length	Rolls per box	Box content
414-666	600 10/1,5-2,5	10 mm	1,5-2,5 mm	12 rm	30	360 rm
414-668	600 15/1,5-2,5	15 mm	1,5-2,5 mm	12 rm	20	240 rm
414-669	600 20/1,5-2,5	20 mm	1,5-2,5 mm	12 rm	15	180 rm
414-660	600 10/2-4	10 mm	2-4 mm	12 rm	30	360 rm
414-661	600 15/2-4	15 mm	2-4 mm	12 rm	20	240 rm
414-671	600 20/2-4	20 mm	2-4 mm	12 rm	15	180 rm
414-670	600 10/3-7	10 mm	3-7 mm	7,5 rm	30	225 rm
414-662	600 15/3-7	15 mm	3-7 mm	7,5 rm	20	150 rm
414-664	600 20/3-7	20 mm	3-7 mm	7,5 rm	15	112,5 rm
414-667	600 15/4-9	15 mm	4-9 mm	7,5 rm	20	150 rm
414-672	600 20/4-9	20 mm	4-9 mm	7,5 rm	15	112,5 rm
414-673	600 30/4-9	30 mm	4-9 mm	7,5 rm	10	75 rm
414-663	600 15/5-12	15 mm	5-12 mm	5 rm	20	100 rm
414-665	600 20/5-12	20 mm	5-12 mm	5 rm	15	75 rm
414-674	600 30/5-12	30 mm	5-12 mm	5 rm	10	50 rm
414-675	600 20/7-15	20 mm	7-15 mm	4,3 rm	15	64,5 rm
414-676	600 25/7-15	25 mm	7-15 mm	4,3 rm	12	51,6 rm
414-677	600 30/7-15	30 mm	7-15 mm	4,3 rm	10	43 rm
414-681	600 20/8-20	20 mm	8-20 mm	3 rm	15	45 rm
414-678	600 25/8-20	25 mm	8-20 mm	3 rm	12	36 rm
414-679	600 30/8-20	30 mm	8-20 mm	3 rm	10	30 rm

Other dimensions on request

Hannoband BG2

for outdoor applications on concealed joints

Hannoband BG2 meets all requirements for concealed pre-compressed joint sealing tapes both for window installation as well as for facade sealing and other (construction) connection joints.

- meets the requirements of DIN 18542 (BG2) and ÖNORM B 5320
- driving rain tightness: ≥ 300 Pa, many other dimensions up to 600 Pa
- airtight: $a_n < 1.0$
- vapor-permeable: s_d value: ≤ 0.5 m
- excellent thermal insulation; thermal conductivity: $\lambda = 0,0396$ W/mK
- normally flammable according to EN 13501
- compatible with conventional building materials
- storage stability: 24 months
- very low emission – EMI CODE EC1^{PLUS}



Item no.	Order designation	Joint depth	Joint width	Roll length	Rolls per box	Box content
413-063	BG2 9/1	9 mm	1 mm	10 rm	33	330 rm
413-030	BG2 10/1,5-2,5	10 mm	1,5-2,5 mm	18 rm	30	540 rm
413-038	BG2 15/1,5-2,5	15 mm	1,5-2,5 mm	18 rm	20	360 rm
413-072	BG2 20/1,5-2,5	20 mm	1,5-2,5 mm	18 rm	15	270 rm
413-028	BG2 10/2-4	10 mm	2-4 mm	12 rm	30	360 rm
413-034	BG2 15/2-4	15 mm	2-4 mm	12 rm	20	240 rm
413-033	BG2 20/2-4	20 mm	2-4 mm	12 rm	15	180 rm
413-044	BG2 15/3-7	15 mm	3-7 mm	6 rm	20	120 rm
413-046	BG2 20/3-7	20 mm	3-7 mm	6 rm	15	90 rm
413-010	BG2 15/5-9	15 mm	5-9 mm	5 rm	20	100 rm
413-011	BG2 20/5-9	20 mm	5-9 mm	5 rm	15	75 rm
413-012	BG2 30/5-9	30 mm	5-9 mm	5 rm	10	50 rm
413-058	BG2 15/7-12	15 mm	7-12 mm	5 rm	20	100 rm
413-059	BG2 20/7-12	20 mm	7-12 mm	5 rm	15	75 rm
413-062	BG2 25/7-12	25 mm	7-12 mm	5 rm	12	60 rm
413-064	BG2 30/7-12	30 mm	7-12 mm	5 rm	10	50 rm
413-066	BG2 20/8-15	20 mm	8-15 mm	4 rm	15	60 rm
413-067	BG2 25/8-15	25 mm	8-15 mm	4 rm	12	48 rm
413-069	BG2 30/8-15	30 mm	8-15 mm	4 rm	10	40 rm

Other dimensions on request

Hannoband THERM

excellent heat and sound insulation from the roll

Hannoband THERM insulates reliably and long-term and provides optimum thermal and sound insulation at lift-and-slide doors and roller shutters, as well as where PU can foams should be avoided, for example, for ecological reasons. Complements perfectly with INSEBO® sealants, foil tapes or Hannoband BG1 and BG2.

- the first choice where PU foams or propellants should be avoided
- Ideal for pressure-free sound and heat insulation
- excellent joint sound insulation: $R_{S,w}$ up to 62 dB*

- excellent thermal insulation; thermal conductivity: $\lambda=0.0396$ W/mK
- normally flammable according to EN 13501
- very low emission – EMICODE EC1^{PLUS}

*70/5-24 was tested with outer and inner foil tape in a 10 mm joint



Item no.	Order designation	Joint depth	Joint width	Roll length	Rolls per box	Box content
412-060	THERM 56/2-8	56 mm	2-8 mm	18 rm	5	90 rm
412-061	THERM 66/2-8	66 mm	2-8 mm	18 rm	4	72 rm
412-062	THERM 76/2-8	76 mm	2-8 mm	18 rm	3	54 rm
412-063	THERM 100/2-8	100 mm	2-8 mm	18 rm	3	54 rm
412-064	THERM 150/2-8	150 mm	2-8 mm	18 rm	2	36 rm
412-065	THERM 200/2-8	200 mm	2-8 mm	18 rm	1	18 rm
412-066	THERM 56/5-24	56 mm	5-24 mm	6 rm	5	30 rm
412-067	THERM 66/5-24	66 mm	5-24 mm	6 rm	4	24 rm
412-068	THERM 76/5-24	76 mm	5-24 mm	6 rm	3	18 rm
412-080	THERM 86/5-24	86 mm	5-24 mm	6 rm	3	18 rm
412-069	THERM 100/5-24	100 mm	5-24 mm	6 rm	3	18 rm
412-070	THERM 150/5-24	150 mm	5-24 mm	6 rm	2	12 rm
412-071	THERM 200/5-24	200 mm	5-24 mm	6 rm	1	6 rm
412-072	THERM 56/8-40	56 mm	8-40 mm	5 rm	5	25 rm
412-073	THERM 66/8-40	66 mm	8-40 mm	5 rm	4	20 rm
412-074	THERM 76/8-40	76 mm	8-40 mm	5 rm	3	15 rm
412-078	THERM 86/8-40	86 mm	8-40 mm	5 rm	3	15 rm
412-075	THERM 100/8-40	100 mm	8-40 mm	5 rm	3	15 rm
412-076	THERM 150/8-40	150 mm	8-40 mm	5 rm	2	10 rm
412-079	THERM 175/8-40	175 mm	8-40 mm	5 rm	1	5 rm
412-077	THERM 200/8-40	200 mm	8-40 mm	5 rm	1	5 rm
412-081	THERM 56/9-50	56 mm	9-50 mm	4 rm	5	20 rm
412-082	THERM 66/9-50	66 mm	9-50 mm	4 rm	4	16 rm
412-083	THERM 76/9-50	76 mm	9-50 mm	4 rm	3	12 rm
412-084	THERM 86/9-50	86 mm	9-50 mm	4 rm	3	12 rm
412-085	THERM 100/9-50	100 mm	9-50 mm	4 rm	3	12 rm
412-086	THERM 150/9-50	150 mm	9-50 mm	4 rm	2	8 rm
412-087	THERM 175/9-50	175 mm	9-50 mm	4 rm	1	4 rm
412-088	THERM 200/9-50	200 mm	9-50 mm	4 rm	1	4 rm

Other dimensions on request

Hannoband 3E Basic

multifunctional tape for window connections

Hannoband 3E Basic is a pre-compressed and impregnated multifunctional joint sealing tape with at least one functional membrane. The different tape widths and thicknesses enable a great variety of Joint widths and window profile thicknesses to be sealed. Hannoband 3E Basic is used for sealing the functional areas of the window connection and is designed for covered applications.

- complies with DIN 18542 (MF2) and ÖNORM B 5320
- meets the requirements for the airtight and impact rain proof sealing
- ideally suited for standard-compliant window installation: heat and sound-proofed and also airtight and impact rain proof
- driving rain tightness: ≥ 600 Pa
- airtight: $a_n < 0.1$
- joint sound insulation: $R_{S,w}$ 57 dB
- excellent thermal insulation; thermal conductivity: $\lambda \leq 0,0386$ W/mK
- normally flammable according to EN 13501
- very low emission – EMICODE EC1^{PLUS}



Item no.	Order designation	Joint depth	Joint width	Roll length	Rolls per box	Box content
417-060	3E Basic 56/4-9 mm*	56 mm	4-9 mm	18,8 rm	5	94,0 rm
417-061	3E Basic 56/6-15 mm*	56 mm	6-15 mm	14,1 rm	5	70,5 rm
417-062	3E Basic 56/10-20 mm*	56 mm	10-20 mm	11,7 rm	5	58,5 rm
417-063	3E Basic 56/15-30 mm*	56 mm	15-30 mm	9,4 rm	5	47,0 rm
417-064	3E Basic 64/4-9 mm	64 mm	4-9 mm	18,8 rm	4	75,2 rm
417-065	3E Basic 64/6-15 mm	64 mm	6-15 mm	14,1 rm	4	56,4 rm
417-066	3E Basic 64/10-20 mm	64 mm	10-20 mm	11,7 rm	4	46,8 rm
417-067	3E Basic 64/15-30 mm	64 mm	15-30 mm	9,4 rm	4	37,6 rm
417-068	3E Basic 74/4-9 mm*	74 mm	4-9 mm	18,8 rm	4	75,2 rm
417-069	3E Basic 74/6-15 mm*	74 mm	6-15 mm	14,1 rm	4	56,4 rm
417-070	3E Basic 74/10-20 mm	74 mm	10-20 mm	11,7 rm	4	46,8 rm
417-071	3E Basic 74/15-30 mm	74 mm	15-30 mm	9,4 rm	4	37,6 rm
417-072	3E Basic 84/4-9 mm*	84 mm	4-9 mm	18,8 rm	3	56,4 rm
417-073	3E Basic 84/6-15 mm	84 mm	6-15 mm	14,1 rm	3	42,3 rm
417-074	3E Basic 84/10-20 mm	84 mm	10-20 mm	11,7 rm	3	35,1 rm
417-075	3E Basic 84/15-30 mm	84 mm	15-30 mm	9,4 rm	3	28,2 rm
417-076	3E Basic 94/4-9 mm*	94 mm	4-9 mm	18,8 rm	3	56,4 rm
417-077	3E Basic 94/6-15 mm*	94 mm	6-15 mm	14,1 rm	3	42,3 rm
417-078	3E Basic 94/10-20 mm*	94 mm	10-20 mm	11,7 rm	3	35,1 rm
417-079	3E Basic 94/15-30 mm*	94 mm	15-30 mm	9,4 rm	3	28,2 rm

*Minimum order quantity: 12 boxes or a multiple of this quantity


Vorlegeband

PE sealing tape, adhesive layer covered with foil

- foamed, closed-cell, plasticizer-free glazing tape
- sealing of windows and doors, thermal and acoustic decoupling of components, e.g. drywall walls, sealing air ducts in air conditioning and ventilation
- one-sided self-adhesive
- adhesive surface remains protected by the PE film until processing
- excellent thermal insulation; thermal conductivity: $\lambda = 0,038 \text{ W/mK}$
- density: approx. 33 kg / m^3
- color: black

Artikelnr.	Bestellbezeichnung	Stärke	Breite	Rollenlänge
409-004	Vorlegeband schwarz 2x10	2 mm	10 mm	20 lfm
409-005	Vorlegeband schwarz 2x12	2 mm	12 mm	20 lfm
409-006	Vorlegeband schwarz 2x15	2 mm	15 mm	20 lfm
409-007	Vorlegeband schwarz 2x20	2 mm	20 mm	20 lfm
409-008	Vorlegeband schwarz 2x30	2 mm	30 mm	20 lfm
409-016	Vorlegeband schwarz 3x10	3 mm	10 mm	20 lfm
409-017	Vorlegeband schwarz 3x12	3 mm	12 mm	20 lfm
409-018	Vorlegeband schwarz 3x15	3 mm	15 mm	20 lfm
409-019	Vorlegeband schwarz 3x20	3 mm	20 mm	20 lfm
409-021	Vorlegeband schwarz 3x30	3 mm	30 mm	20 lfm
409-023	Vorlegeband schwarz 3x50	3 mm	50 mm	20 lfm
409-025	Vorlegeband schwarz 3x60	3 mm	60 mm	20 lfm
409-030	Vorlegeband schwarz 4x10	4 mm	10 mm	20 lfm
409-031	Vorlegeband schwarz 4x12	4 mm	12 mm	20 lfm
409-032	Vorlegeband schwarz 4x15	4 mm	15 mm	20 lfm
409-033	Vorlegeband schwarz 4x20	4 mm	20 mm	20 lfm
409-035	Vorlegeband schwarz 4x30	4 mm	30 mm	20 lfm
409-038	Vorlegeband schwarz 4x50	4 mm	50 mm	20 lfm
409-044	Vorlegeband schwarz 5x10	5 mm	10 mm	10 lfm
409-045	Vorlegeband schwarz 5x12	5 mm	12 mm	10 lfm
409-046	Vorlegeband schwarz 5x15	5 mm	15 mm	10 lfm
409-047	Vorlegeband schwarz 5x20	5 mm	20 mm	10 lfm
409-049	Vorlegeband schwarz 5x30	5 mm	30 mm	10 lfm
409-051	Vorlegeband schwarz 5x50	5 mm	50 mm	10 lfm
409-061	Vorlegeband schwarz 6x40	6 mm	40 mm	10 lfm
409-062	Vorlegeband schwarz 6x50	6 mm	50 mm	10 lfm
409-084	Vorlegeband schwarz 6x60	6 mm	60 mm	10 lfm
409-077	Vorlegeband schwarz 10x40	10 mm	40 mm	10 lfm
409-078	Vorlegeband schwarz 10x50	10 mm	50 mm	10 lfm

andere Abmessungen auf Anfrage



Vorlegeband Extra

PE sealing tape, self-adhesive on one side, without additional foil

- foamed, closed-cell, plasticizer-free glazing tape
- glazing tape for window glazings, sealings of windows and doors, thermal and acoustic decoupling of components, e.g. dry construction stud walls, sealing of air ducts in air conditioning and ventilation systems
- one-sided self-adhesive
- supplied with internal adhesive layer - the removal and disposal of the protective film is omitted (unlike Vorlegeband)
- excellent thermal insulation; thermal conductivity: $\lambda = 0,034 \text{ W/mK}$
- density: approx. 33 kg / m^3
- compression hardness 25%: 38 kPa
- color: black

Artikelnr.	Bestellbezeichnung	Stärke	Breite	Rollenlänge
409-317	Vorlegeband Extra schwarz 2x6	2 mm	6 mm	25 lfm
409-300	Vorlegeband Extra schwarz 2x9	2 mm	9 mm	25 lfm
409-316	Vorlegeband Extra schwarz 2x12	2 mm	12 mm	25 lfm
409-312	Vorlegeband Extra schwarz 2x20	2 mm	20 mm	25 lfm
409-337	Vorlegeband Extra schwarz 2x25	2 mm	25 mm	25 lfm
409-301	Vorlegeband Extra schwarz 3x9	3 mm	9 mm	25 lfm
409-306	Vorlegeband Extra schwarz 3x12	3 mm	12 mm	25 lfm
409-313	Vorlegeband Extra schwarz 3x20	3 mm	20 mm	25 lfm
409-319	Vorlegeband Extra schwarz 3x30	3 mm	30 mm	25 lfm
409-320	Vorlegeband Extra schwarz 3x40	3 mm	40 mm	25 lfm
409-326	Vorlegeband Extra schwarz 3x50	3 mm	50 mm	25 lfm
409-302	Vorlegeband Extra schwarz 4x9	4 mm	9 mm	25 lfm
409-311	Vorlegeband Extra schwarz 4x12	4 mm	12 mm	25 lfm
409-307	Vorlegeband Extra schwarz 4x15	4 mm	15 mm	25 lfm
409-339	Vorlegeband Extra schwarz 4x25	4 mm	25 mm	25 lfm
409-335	Vorlegeband Extra schwarz 4x30	4 mm	30 mm	25 lfm
409-303	Vorlegeband Extra schwarz 5x9	5 mm	9 mm	10 lfm
409-340	Vorlegeband Extra schwarz 5x25	5 mm	25 mm	10 lfm
409-336	Vorlegeband Extra schwarz 5x30	5 mm	30 mm	25 lfm
409-344	Vorlegeband Extra schwarz 5x40	5 mm	40 mm	10 lfm
409-304	Vorlegeband Extra schwarz 6x9	6 mm	9 mm	10 lfm
409-310	Vorlegeband Extra schwarz 6x15	6 mm	15 mm	10 lfm
409-329	Vorlegeband Extra schwarz 6x20	6 mm	20 mm	10 lfm

andere Abmessungen auf Anfrage

Folienband DUO Easy 240

self-adhesive foil tape for the inner and outer joint


- for sealing the building connection joint inside AND outside
- compensation of movements due to elasticity of the foil tape
- optimal use even with hinged window elements
- suitable for refurbishment and new construction
- system tested according to ÖNORM B 5320
- humidity-variable s_d value: 0.48 to 12 m - depending on the ambient conditions
- driving rain tightness: > 1.050 Pa
- airtight: $a_n < 0.1$
- high adhesive strength of the fastening strip
- 12 months UV resistant
- can be easily plastered and painted over
- reversible for a short time
- shelf life: 24 months
- meets the requirements of ecological building materials (contains no phthalates, halogen compounds, flame retardants, etc.)
- very low emission – EMICODE EC1^{PLUS}
- DUO Easy+ has an additional adhesive tape on the backside.



Item number	Order designation	Roll length	Rolls per box	Box content
509-280	DUO Easy 240, 75 mm	25 rm	5	125 rm
509-281	DUO Easy 240, 100 mm	25 rm	4	100 rm
509-282	DUO Easy 240, 150 mm	25 rm	2	50 rm
509-283	DUO Easy 240, 200 mm	25 rm	2	50 rm
509-285	DUO Easy 240, 300 mm	25 rm	1	25 rm
509-290	DUO Easy+ 240, 75 mm	25 rm	5	125 rm
509-291	DUO Easy+ 240, 100 mm	25 rm	4	100 rm
509-292	DUO Easy+ 240, 150 mm	25 rm	2	50 rm
509-293	DUO Easy+ 240, 200 mm	25 rm	2	50 rm
509-294	DUO Easy+ 240, 300 mm	25 rm	1	25 rm

Other dimensions on request

How to install foil tape



Folienband FA Easy Soft 240

full-surface adhesive foil tape for the outer joint

- for sealing the outside construction joint according to ÖNORM B 5320
- system tested according to ÖNORM B 5320
- vapor permeable; s_d value: 0,8 m
- driving rain tightness: up to 1.050 Pa
- high adhesive power
- can be easily plastered over
- very low emission – EMICODE EC1^{PLUS}
- FA Easy+ Soft has an additional adhesive tape on the backside



Item number	Order designation	Roll length	Rolls per box	Box content
509-721	FA Easy Soft 240, 75 mm	25 rm	5	125 rm
509-722	FA Easy Soft 240, 100 mm	25 rm	4	100 rm
509-724	FA Easy Soft 240, 150 mm	25 rm	2	50 rm
509-726	FA Easy Soft 240, 200 mm	25 rm	2	50 rm
509-728	FA Easy Soft 240, 300 mm	25 rm	1	25 rm
509-731	FA Easy+ Soft 240, 75 mm	25 rm	5	125 rm
509-732	FA Easy+ Soft 240, 100 mm	25 rm	4	100 rm
509-734	FA Easy+ Soft 240, 150 mm	25 rm	2	50 rm
509-736	FA Easy+ Soft 240, 200 mm	25 rm	2	50 rm
509-738	FA Easy+ Soft 240, 300 mm	25 rm	1	25 rm

Other dimensions on request

Minimum order quantity: 150 mm: 1.000 rm; 200 mm: 700 rm; 300 mm: 500 rm

Folienband FI Easy 240

full-surface adhesive foil tape for the inner joint

- for sealing the inside construction joint according to ÖNORM B 5320
- vapor diffusion restraining: s_d value: > 10 m
- airtight: $a_n < 0.1$
- suitable for renovation and new construction
- high adhesive power
- can be easily plastered over
- shelf life: 24 months
- very low emission – EMICODE EC1^{PLUS}
- FI Easy+ has an additional adhesive tape on the backside



Item number	Order designation	Roll length	Rolls per box	Box content
509-701	FI Easy 240, 75 mm	25 rm	5	125 rm
509-702	FI Easy 240, 100 mm	25 rm	4	100 rm
509-706	FI Easy 240, 200 mm	25 rm	2	50 rm
509-708	FI Easy 240, 300 mm	25 rm	1	25 rm
509-711	FI Easy+ 240, 75 mm	25 rm	5	125 rm
509-712	FI Easy+ 240, 100 mm	25 rm	4	100 rm
509-716	FI Easy+ 240, 200 mm	25 rm	2	50 rm
509-718	FI Easy+ 240, 300 mm	25 rm	1	25 rm

Other dimensions on request

Minimum order quantity: 100 mm: 100 rm; 200 mm: 700 rm; 300 mm: 500 rm

Anschlussflansch

for connecting the window-sealing to the building-waterproofing


- used to create a water-stopping connection for floor-to-ceiling window and door elements
- excellent adhesion to all commercially available surfaces and bitumen
- available for mounting on both sides or one side
- meets the requirements of ÖNORM B 3691, ÖNORM B 3692 and DIN 18533
- size 200 x 300 mm

Item number	Order designation
407-900	Set Anschlussflansch alternating
407-901	Set Anschlussflansch one-sided

Packaging unit: 1 set contains: 16 x Anschlussflansch, 1 x cartridge 290 ml Flanschdicht, 16 x plaster fleece, 16 x screw units (4 x wood screws and 4 x screws with drill bit), 1 assembly instruction, 1 processing instruction

3 Easy Steps to the Perfect Connection:

- Apply a bead of „Flanschdicht“ to the groove of the „Anschlussflansch“ and then attach it to the window or door element with 4 screws.
- Place the „Anschlussflansch“ at least 150 mm above the finished floor level (FFL) and flush with the outer side of the window or door element.
- Ensure that the „Anschlussflansch“ is bonded to the building structure (masonry) without wrinkles or tension.



The following products can be used to make the connection on the INSEBO® Anschlussflansch backwater-tight:

Liquid seals:

- Frankosil 1K und Frankolon 2K
- REVOPUR WP 200
- Triflex PRODetail, Triflex Smartec
- RALMO-Flüssigabdichtung ÖKO
- Kemperol 2K PUR
- Botament RD2 The Green One und Botament RD1 Universal
- Remmers MB 2K
- SikaFloor 405 und Sika IgoDicht 2K-P
- Sopro Dichtschlämme Flex RS 623, Sopro Turbo-Dichtschlämme 2K TDS 823, Sopro ZR-Turbo Reaktivabdichtung, Sopro ZR Turbo XXL Reaktivabdichtung 2-K 618, Sopro ZR-Turbo Max sowie Sopro KellerDicht 1K KD 752 und Sopro KellerDicht 2K KD 754
- maxit AD-1K-Außendicht und maxit SDS 16
- Hahne - IMBERAL DAB 30P und DAKORIT PUR1K 30P
- Enkolan Abdichtung 1K LF, Enkopas, Enkryl
- Wecryl 110
- Elapro 1K-Sil

- Bauder LIQUITEC PU
- weber.tec Superflex D2 und weber.tec Superflex D24
- Kaubiflex FA Dichtschlämme 1K und 2K, Kaubiflex FA Dichtschlämme AS 1K und 2K, Kaubiflex FA 2K TT-Flex
- WIDOCRYL-Detail
- PCI Barraseal Turbo
- PCMB PCI Pecimor 2K

Linings:

- RALMO-Tape 4000, RALMO-EPDM
- TOPLINE-Türanschlussband
- Bitumenbahnen (kalt oder geflämmt)

insebo.com

Flanschdicht

sealant and adhesive for INSEBO® Anschlussflansch

- waterproof and airtight after curing
- very good adhesion on purenite, bitumen and PE
- very good paintability according to DIN 52452
- for interior and exterior use
- weather resistant
- solvent, isocyanat and silicone free
- one cartridge is included in each Anschlussflansch set

Item number	Order designation	Content
407-902	Flanschdicht	290 ml cartridge
Packing unit: 12 cartridges/box		



Folienprimer

primer for foil tapes on porous surfaces

- first coat for foil tapes
- applicable with Folienband DUO Easy 240, Folienband FI Easy 240 and Folienband FA Easy Soft 240
- for absorbent substrates
- ready-to-use mixture for application with a brush
- solventless
- free of plasticizers
- colorless

Item number	Order designation	Content
509-500	Folienprimer	400 ml
Packing unit: 8 pieces/box		



PRODUCT OVERVIEW

LUBRICANTS, SPRAYS & CLEANERS

Assistants in bottles and cans: Lubricants, sprays, and cleaners simplify life, building, and renovation.

Our special products complement our product range and simplify various tasks - whether on woodworking machines, in molding and injection molding, or in the cleaning of PVC window profiles.

- 74 Zinkspray
- 74 Kunststoffreiniger
- 74 Iso-Pro Clean **NEW!**
- 75 Silikonspray
- 75 Gleitmittel M

For more information about our products and the correct application please observe our technical and safety data sheets which you can read and download conveniently on our website (insebo.com).

Zinkspray

temperature resistant corrosion protection

- for quick repairs of damaged zinc layers as well as damaged areas on galvanized steel parts
- for the renewal of destroyed primers
- extensive rust protection coating
- good electrical conductivity - therefore usable as spot paint on welded seams
- fast curing
- can also be used without primer



Item number	Order designation	Content
303-005	Zinkspray 400 ml	400 ml spray can
Packing unit: 12 spray cans/box		

Kunststoffreiniger

dissolves grease, oil and dirt

- special cleaner for PVC window profiles and other plastics
- Improves the adhesion of sealants in many cases
- for removal of contaminants resulting from processing, transport or assembly - stains, pencil marks etc.
- suitable for removing uncured silicone residues
- color:less
- perform compatibility test before use
- only for professional and industrial use (not for private users)



Item number	Order designation	Content
304-052	Kunststoffreiniger 1 l	1 l metal canister
Packing unit: 3 metal canisters/box		

Iso-Pro Clean

gentle cleaning and degreasing

- fast residue-free evaporation
- for gentle cleaning of electrical and mechanical components
- suitable for the removal of uncured MS residues
- degreasing of various materials, such as plastic surfaces, metals, etc.

NEW PRODUCT



Item number	Order designation	Content
304-055	Iso-Pro Clean	500 ml spray can
Packing unit: 12 spray cans/box		

Silikonspray

lubricates stain-free and invisible

- oil and grease-free protective, lubricating and release agent and care product
- suitable for plastics, wood, rubber and metals
- excellent release agent for molding and injection molding, as an assembly aid for hose connections as well as in wood and paper processing
- for lubricating cylinder locks, hinges, car door seals, sunroofs, seat rails and safety belt winders
- clean, resin-free sliding and lubricant film
- good temperature resistance
- protects against oxidation and corrosion
- water repellent and antistatic



Item number	Order designation	Content
301-001	Silikonspray 300 ml	300 ml spray can
Packing unit: 12 spray cans/box		

Gleitmittel M

for woodworking machines and many other applications

- lets wood glide effortlessly when working on planers, milling machines, assembly tables, etc.
- silicone-free, therefore no impairment when pickling, varnishing, veneering or gluing
- ready to use
- colorless
- only for professional and industrial use (not for private users)



Item number	Order designation	Content
302-058	Gleitmittel M 5 l	5 l metal canister
Packing unit: 2 metal canisters/box		

PRODUCT OVERVIEW

PROCESSING TOOLS

**Properly dosed, precisely glued, perfectly pressed:
our processing tools make it easier.**

Even INSEBO® products do not apply themselves on their own - that is why we have expanded our range of processing tools: Discover a whole world of presses for cartridges and aluminium bags as well as guns for PU foam cans.

- 78 PU-Schaum-Pistole 2000
- 78 Dosierpistole Metall Lite Plus
- 79 Dosierpistole Guardia X7
- 79 Scuro Evo 6
- 79 Dosierpistole Metall Lite XL
- 80 Kartuschenpresse eXcePt-310
- 80 Halbschalenpresse HPS56
- 80 Skelettpresse X7
- 81 Profi-Kartuschenpresse XP-DELTA
- 81 Kartuschenpresse FX7-90
- 81 Alurohrpresse FX7-60
- 82 Druckluftpresse B600
- 83 Mörtelpresse X7-1000
- 83 Fugenspachtel-Set
- 83 Universal-Fugenspachtel

For more information about our products and the correct application please observe our technical and safety data sheets which you can read and download conveniently on our website (insebo.com).

PU-Schaum-Pistole 2000

the dispensing gun for the best foam quality

- high quality dispensing gun with brass setting wheel and metal ball in the valve
- exact dosing and optimal foam quality
- for inaccessible areas, two extension tubes and two tips for narrow openings are included
- the plastic tubes supplied in the original box are to be used for exposed areas that can not be reached directly with the dispensing gun
- brass tips especially made for the PU-Schaum-Pistole 2000 can be ordered additionally. They are suitable for particularly narrow and deep joints. The brass tips are available as 5-cm- or 20-cm-version packed in sets of 5 pieces including the packaging in hangers.



PU-Schaum-Pistole 2000 with INSEBO® Logo



PU-Schaum-Pistole 2000 with company neutral layout

Item number	Order designation	Note
113-012	PU-Schaum-Pistole 2000 INSEBO®	with INSEBO® Logo
113-003	PU-Schaum-Pistole 2000	company neutral
113-035	Screw-on tip for dispensing gun 5 cm 5-piece-set	
113-036	Screw-on tip for dispensing gun 20 cm 5-piece-set	



Dosierpistole Metall Lite Plus

high-quality metal gun with chrome-plated transport tube

- solid metal foam gun
- PTFE coated needle and can adaptor
- large brass adjusting screw
- tapered extrusion tube for high
- rubberized handle for superior grip



Item number	Order designation
610-005	Dosierpistole Metall Lite Plus

Dosierpistole Guardia X7

the professional processing tool for precise work

- new, solid construction
- complete stickresistant PTFE-coating
- optimized, stronger can adaptor
- very good foam flow
- precise foam adjusting with endstop-function
- rubber-coated handle and trigger



Item number	Order designation
610-006	Dosierpistole Guardia X7

Scuro Evo 6

completely non-stick coated and high-quality metal gun

- high-quality metal gun
- completely non-stick coated
- brass tip thread
- low weight
- brass pistol attachment 5 cm
- 4-fold long-life seal
- easy and precise adjustment with quick-stop function in the trigger
- magazine with 2 brass tips
- ergonomic handle



Item number	Order designation
610-016	Scuro Evo 6

Dosierpistole Metall Lite XL

the extra long foam gun for special applications

- sturdy metal foam applicator with 60cm tube
- rubber coated handle
- non-slip brass adjusting knob
- developed for the filling of wall openings, effortless working in confined spaces and foaming without a ladder



Item number	Order designation
610-009	Dosierpistole Metall Lite XL

Kartuschenpresse eXcePt-310

robust cartridge press with strong transmission ratio

- integrated afterflow-stop function
- also optimally suited for viscous sealants and adhesives
- pleasant working due to rubberized handle
- integrated nozzle cutting knife
- corrosion protected push and drive parts
- with practical ladder hook
- transmission ratio 19: 1



Item number	Order designation
621-009	Kartuschenpresse eXcePt-310

Profi-Kartuschenpresse XP-DELTA

highest quality with switchable trigger ratios

- rotary carriage and ladder hook
- rubber-coated handle and trigger
- anticorrosive performance
- activatable dripless function
- DELTA catch plate, extremely tough and durable
- switchable trigger ratios: 25:1 and 12:1



Item number	Order designation
621-012	Profi-Kartuschenpresse XP-DELTA

Halbschalenpresse HPS56

low weight and good transmission ratio

- compact and ergonomic design and simple one-handed operation for fatigue-free working
- easy and quick cartridge exchange
- no afterflowing of the sealant or adhesive by activating the backstop with a press of the thumb
- for sealant and adhesive cartridges
- with practical ladder hook
- transmission ratio 13: 1



Item number	Order designation
621-006	Halbschalenpresse HPS56

Kartuschenpresse FX7-90

high-quality sealant press for especially viscous sealants

- rotary carriage
- rubber-coated handle and trigger
- double slide bearings for smooth-running function
- multiple-strength thrust block
- ladder hook
- for high viscosity dispensing material
- trigger ratio 17:1



Item number	Order designation
621-008	Kartuschenpresse FX7-90

Skelettpresse X7

handy cartridge press for do-it-yourselfers and professionals

- low weight, handy cartridge press
- no afterflowing during work interruptions due to automatic tension release
- for sealant and adhesive cartridges
- includes needle for piercing the cured foam in the nozzle
- with practical ladder hook
- transmission ratio 7:1



Item number	Order designation	Color
621-004	Skelettpresse X7	black

Alurohrpresse FX7-60

high quality for cartridges and aluminium bags

- rotary carriage
- aluminum union nuts
- rubber-coated handle and trigger
- double slide bearings for smooth running function
- multiple-strength thrust block
- push plate optimized for complete emptying
- for high viscosity dispensing material
- trigger ratio 17:1



Item number	Order designation
622-009	Alurohrpresse FX7-60

Druckluftpresse B600

handy, easy to operate sealant press for effortless application

- anodized aluminium tube
- optimized centre of gravity axis
- minimal air consumption
- working pressure 6-10 bar
- easy pressure regulation and excellent dosage adjustment

Item number	Order designation
622-013	Druckluftpresse B600





Mörtelpresse X7-1000

for exactly filled mortar joints

- for optimal processing of grout
- not suitable for masonry mortar, screed and other coarse-grained mixtures
- joints can be completely filled without dirt around the edge
- available wearing parts (plastic filling tube, piston rubber, replacement tips)
- dosing tip with small opening for narrow, fine joints
- dosing tip with large opening for wider joints
- filling capacity: approx. 1.000 ml
- Wide chatch plate
- metal screw connection with handle
- rubber-coated handle and trigger
- retaining clip secures tube
- with metal shovel for easy filling

Item number	Order designation
630-001	Mörtelpresse X7-1000



Fugenspachtel-Set

practical spatulas for small and large joints

- one piece triangular-shaped (3, 5 and 9 mm)
- one piece round-shaped (6, 8, 10 and 14 mm)
- two pieces triangular-shaped (6, 8, 10 and 14 mm)
- made of robust special plastic
- for square and round joints
- for fast and clean grouting
- for an optimal, clean joint pattern

Item number	Order designation
213-020	Fugenspachtel-Set



Universal-Fugenspachtel

with practical rounding

- universal joint spatula for all sealants
- for easy smoothing of the joint surface
- fast, easy, clean, cost-saving
- suitable as silicone smoothing spatula for professional users
- dimension: approx. 5,8 cm x 11,4 cm

Item number	Order designation
213-001	Universal-Fugenspachtel



GENERAL SALES CONDITIONS

■ 1. General Regulations

All offers, deliveries and agreements are based exclusively on our general sales conditions.

Contrary statements on the part of the buyer indicating his own terms of business and purchase are herewith contradicted. Also, they shall not legally bind us, if the buyer declares his conditions as exclusive and we have not again objected to them at the time of the formation of the contract. Even without the written confirmation of the buyer, our conditions shall be deemed to have been fully accepted at the latest, when our goods or services are taken delivery of.

■ We reserve the rights of ownership and copyright in illustrations, drawings, calculations and other documents. These documents shall not be made accessible to third parties.

■ 2. Terms of payment

All payments are to be made by the purchaser directly to us. Our sales representatives are only authorized to receive payment if they have been granted explicit written authorization from us for a specific case.

■ Unless otherwise agreed upon, the following applies: payment in full, without any deductions, is due within 20 days. Bills of exchange and cheques will not be accepted

■ If the agreed payment period is exceeded, we reserve the right to charge interest at the current valid default interest rate, but at least at a rate of 12% per annum, with interest capitalized quarterly. Additionally, the buyer is responsible for paying adequate reminder charges and collection costs of all sorts. This does not preclude the assertion of any further claims.

■ If the purchaser is overdue with a payment for longer than 10 days, the entire sum of all outstanding debts will become immediately due for payment after a written reminder. After setting an appropriate period of grace, we are entitled to withdraw from the agreement and demand return of the goods delivered.

■ Any delay of payments or settling of accounts due to eventual disputed counterclaims from the buyer are not valid.

■ 3. Reservation of title

All delivered goods shall remain our property (reserved goods) until the ordering party has fulfilled all payment obligations. The reservation of title also relates to the new products, which are produced by processing or combination of our goods. If the buyer resells the products within the framework of a proper business transaction, all claims from the resale amounting to our demands is given to us. Upon request, the purchaser is obliged to inform us of the name of the third party debtor and the amount of the claim against this one.

■ The customer should notify us without undue delay of any third-party seizure. Pledging of the goods by the customer is not permitted.

■ 4. Trade mark rights

In contract manufacturing with predetermined prescriptions and equipment the purchaser has the responsibility that no copyrights of third parties are violated by the production and supply of the goods. The buyer agrees to indemnify us against claims for damages or other claims by third parties and related costs of all kinds and to reimburse us for direct and indirect damages and expenses incurred from the infringement of any proprietary rights.

■ 5. Delivery period

Delivery periods quoted by us are not binding, unless these have not been expressly agreed as fixed dates. Furthermore, the specified delivery periods are only insofar binding for us, as we are not prevented by war, breakdowns, shortage of raw materials, transport disruptions or disposal of force majeure from fulfilling the order. Such events entitle us to completely or partially withdraw from the contract without giving the buyer the right to claim damages. If there is no fixed delivery period, the contracting parties are considered to have agreed on „prompt delivery“. However, we reserve the right to extend our delivery time by a maximum of 4 weeks in all cases. If the goods have already been completed on the contractual delivery date and the acceptance is required, they will be stored on our premises at the expense and risk of the purchaser.

Unless specified otherwise by the purchaser, we select what we consider to be the best type of dispatch and the best route of shipment, but without any guarantee. Partial deliveries are permitted. We reserve the right to standard deliveries over and under 5% of the contracted quantities.

■ If the buyer does not accept the quantity of goods in their entirety, we may, without prejudice to any other rights, charge a small order surcharge. For orders under 40,- EUR - a surcharge of 4,- EUR per invoice can be additionally charged.

■ The liability of the delivery and a possibly agreed delivery date apply only if the supply of all raw materials processed in the product is guaranteed. Compensation for late delivery, in particular contractual penalties in delivery contracts or general terms and conditions are expressly excluded.

■ 6. Transfer of risk

In principle, deliveries are made ex works without specially agreed terms of delivery.

■ Our delivery duty shall be deemed to have been wholly fulfilled and the risk shall pass in every aspect to the customer as soon as the goods have left our factory. This also applies in the case, when the goods are delivered by us freight free. Any transport or other insurance coverage shall be the responsibility of the customer. All damages to the goods during transport or missing parts must be noted immediately and confirmed by signature of the delivery person (for example: truck driver). Goods, which is agreed shall be collected by the customer will, from the time at which the customer has been notified of readiness for collection, be preserved at his own risk. If the buyer fails to perform its duty of collection, we may demand reasonable compensation for the storage.

■ 7. Notice of defects

All information about product characteristics is based on our experiences and technical knowledge of our suppliers. They do not release the purchaser and user of application-related aptitude tests. Product liability compensation is excluded in any case.

■ Our technical advice shall be occurring orally, in writing, or by trials to the best of the company's knowledge, but is only considered non-binding advice.

It does however not release the purchaser and user from the duty to check by himself, if the products supplied by are suitable for the intended processes and purposes. Application and processing of the products take place beyond our control possibilities and lie therefore exclusively in the responsibility of customers and users.

■ On pain of losing his entitlement to assert claims, the client must notice defects immediately after the shipment arrives at the destination, correctly, in writing and in detail and documented by submission of samples of the rejected goods. 10 days after the receipt of the shipment no more complaint is admissible. Small commercial or technically unavoidable deviations in colour, size and quality of the equipment cannot be the subject of a complaint. Decisive for quality and workmanship of any order are the average failure patterns, which are presented to the purchaser on his request.

■ In the case of justified reclamation, the buyer has the right to exchange the goods, provided that the claimed goods are in their original condition. In no case, complaints entitle the purchaser to claim for damages, conversion, reduction or withdrawal from the contract.

■ Our data on the properties, processing and application of our products is based on scrupulous tests and practical experience. However, they are without any obligation and do not relieve the buyer from his obligation to ensure himself by adequate tests, that he can achieve the intended result with our products.

Damage claims will only be accepted up to the amount of the value of the goods. Further claims (especially consequential damages and distorted shapes) and claims for consequential costs shall be excluded. No liability - also in patent rights - can be assumed in individual cases.

■ 8. Place of performance and jurisdiction

The place of performance for all of our deliveries is our company headquarters. Performance place for the purchaser's obligations is Himberg near Vienna.